Road Stems





ROAD RACING AHEAD STEM TECHNICAL SPECIFICATIONS:

Material:	Stem:	Wrought 6061T6 aluminum alloy, hand TIG welded solution heat treated & artificially aged
	Pinch bolt::	4340 Cromo, heat treated, zinc plated
	Adjustment bolt:	M6.0 x 1.0, grade 8.8, zinc plated
	Cotter:	7075T6 aluminum
	Cotter bolt::	M6 x 1.0, grade 12.9, zinc plated
	Cap:	Nylon Glass Composite
	Wedgeloc:	Die cast aluminum alloy ,
	Thread:	M6 x 1.0
Weight::	200g - 110mm	
Finish:	Matte black epoxy powdercoat or hand polished	

CLASSIC ROAD RACING STEM TECHNICAL SPECIFICATIONS:

Material:	Stem:	Wrought 6061T6 aluminum alloy, hand TIG welded solution heat treated & artificially aged
	Pinch bolt:	4340 Cromo, heat treated, zinc plated
	Expander bolt:	Ceramic coated Zicral alloy
	Thread:	M8 x 1.0
Weight:	200g - 110mm	
Sizes:	Length:	70 - 150mm x 10mm (110 - 130 x 5mm)
	Angle:	-17.5o 0.0o
	Quill Ø:	22.2mm
	Clamp Ø:	26.0mm, 26.4mm
Finish:		Matte black epoxy powdercoat or hand polished

ROAD STEMS (POLISHED)								
Length (mm)	80	90	100	110	115	120	130	140
-17.5˚ rise	●	●	●	●		●	●	●
0˚ rise	●	●	●	●	●	●	●	●
0˚ rise Ahead			●	●		●	●	
-17˚ rise Ahead			●	●		●	●	
clamp ø 26.0mm & 26.4mm								

ROAD STEMS (BLACK)								
Length (mm)	80	90	100	110	115	120	130	140
-17.5˚ rise	●	●	●	●		●	●	●
0˚ rise	●	●	●	●	●	●	●	●
0˚ rise Ahead			●	●		●	●	
-17˚ rise Ahead			●	●		●	●	
clamp ø 26.0mm & 26.4mm								

syncros®

Syncros Applied Technology

2001 East Dyer Road, Santa Ana, CA 92705-5709, USA

Telephone: (714) 481-2497 • Facsimile: (714) 481-2426 • www.syncros.com