Randonneur Front Rack Installation Instructions

Congratulations on your new front rack! The Randonneur Front Rack is perfect for handlebar bags, dry bags, baskets, and anything else you can zip-tie or strap down.

Part 1: Installing the Lower Mounts



Screw lower tangs to eyelets using 2 * M4 bolts + 2 * washers.

Level rack and snug the eyelet bolts until it doesn't move.

Note 1: If your fork does not have eyelet braze-ons, use p-clamps as substitutes. The included clamps work for most forks, but if your blades are wider or narrower than the included ones, you can find other sizes on the webstore.

Note 2: Since there are varying braze-on positions and clearances among forks, it is ok to bend the struts to fit your needs. Just remember to bend incrementally.

Part 2: Installing the Fork Crown Strut

Hold the bent end of the strut up to the fork crown. Note position of brake, hangers, and other components.

Identify a path for the strut to avoid these interferences. The 90° bend can be face up or face down.



Bend is face down.



Bend is face up for cantilever brakes.

Using your hands, a bench vise, or pliers, bend the tang so it is flush with both the fork crown and the bottom of rack while avoiding any other components.

Insert fork crown bolt through the 90° bend in strut and use the M5 nut + 1 * washer to secure strut to fork crown.

Use 2 * M4 bolts + 2 * M4 washers + 2 * M4 nylock nuts to secure strut to platform.

Ensure everything is level and snug.

Enjoy your new front rack!





Integrated Decaleur Installation Instructions

If you have the Randonneur Rack with Integrated Decaleur, your handlebar bag setup will be simple, secure, and lightweight.

Part 1: Installing the bag mount to your bag

Place bag mount into decaleur.

Place bag onto the rack platform. Ensure your bag is square and level.

Using a Sharpie, mark your bag's position through bag mount's holes.

Follow your bag manufacturers' instructions for creating a hole through the material.

Once the bag mount holes are created, use the included 2 * bolt + 2 * washer + 2 * nylock nut to secure the mount to the bag.

Part 2: How to use the Integrated Decaleur

Now that your bag mount is installed to your bag, taking your bag on and off your rack is a breeze. To put the bag on, slip the bag's backstop strap (if it has one) over the rack's decaleur, line up the prongs with the receiver, and insert.

Note: We suggest using a strap underneath your bag to secure it to the platform, especially if off-road adventures are in your future.

