2004
LeMond
Specifications Manual

U. S. Version

© Copyright Trek Bicycle Corporation 2003
All rights reserved

Table of Contents

Titanium spine

Tete de Course *1*
Victoire *2*
Victoire T *3*

Titanium

Arrivee *4*
Arrivee T *5*

Steel spine

Maillot Jaune *6*
Zurich *7*
Zurich *8*
Zurich T women's *9*
Buenos Aires *10*
Buenos Aires T *11*

Performance aluminum

Alpe d'Huez *12*
Alpe d'Huez *13*
Tourmalet *14*
Tourmalet T *15*
Reno *16*
Reno T *17*
Reno T women's *18*

Comfort

Big Sky SLT *19*
Big Sky SL *20*
Big Sky S *21*

Cross

Poprad *22*

Hybrid

Wayzata *23*

LeMond Tete de Course *3486000*14.093*

FRAMESET

Main tubes	Reynolds butted 3/2.5 Ti/OCLV 110	
Stays	Reynolds butted 3/2.5 Ti/OCLV 110	
Color	Titanium/Carbon Cloth • Blue/White decal • Black fade-to-carbon fork	
Fork	Bontrager Race XXX Lite	371 mm axle-crown length
Headset	Cane Creek S-6 Aheadset, alloy	25.4/34.0/30.0, 27.1 mm stack height

CONTROLS

Handlebar	3TTT Zepp XL	31.8 mm clamp diameter
Stem	3TTT Zepp XL	34.0 mm steerer clamp height
Shift levers	Shimano Dura-Ace STI, Flite Deck compatible	
Brake levers	Integrated brake/shift	
Tape	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano Dura-Ace	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur	Shimano Dura-Ace	
Crankset	Shimano Dura-Ace 53/39	130 mm bolt hole circle
Bottom bracket	Shimano Dura-Ace, integral axle	Integral axle
Chain	Shimano Dura-Ace	10 speed, 108 links
Cassette	Shimano Dura-Ace 11-23, 10spd	

WHEELSET

Front wheel	Bontrager Race X Lite, 20°	592mm E.R.D.
	286 mm radial spokes, Velox 16mm rim strip	
Rear wheel	Bontrager Race X Lite, 24°	595 mm E.R.D.
	291/286 mm 2x/radial rear spokes, Velox 16mm rim strip	
Spokes	DT Aerolite (New Aero rear drive), ProLock alloy nipples	
Front tire	Bontrager Race X Lite, folding	700 x 23c
Rear tire	Bontrager Race X Lite, folding	700 x 23c
Inner tubes	Presta valve	

OTHER

Seatpost	Thomson Elite	27.2 mm outer diameter
Saddle	SSM Aspide, Ti/leather	
Seatpost binder	Alloy w/integral bolt	35.0 mm inner diameter
Brakes	Shimano Dura-Ace	
Pedals	-not supplied-	9/16" axle
Additionals	2 water bottle mounts (1 bottle on 49), pump peg (not on 49, 51, 53)	
Bike weight	16.6 lb/7.54 kg	

FIT *dimensions in MM, unless specified*

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		66.9	68.5	70.5	72.2	73.5	75.3	77.3
	cm	170	174	179	183	187	191	196
Handlebar	width	420	440	440	460	460	460	460
Stem	length	90	100	110	110	120	120	130
	angle	10	10	10	10	10	10	10
Headset spacers		40	40	40	40	40	40	40
Crank	length	170	172.5	172.5	175	175	175	175
Seatpost	length	330	330	330	330	330	330	330
Steerer	length	187.1	199.1	216.1	235.1	253.1	271.6	289.6

GEOMETRY *dimensions in MM, unless specified*

Head tube angle	72.0	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	63	60	57	59	59	56	56
Seat tube angle	74.0	73.8	73.3	73.0	72.5	72.5	72.0
Effective top tube	525	532	545	565	575	591	606
Seat tube	488	498	512	528	542	560	573
Standover	728	741	754	772	785	803	815
Wheelbase	968	969	975	984	989	1000	1011
Bottom bracket height	264	266	266	269	269	269	269
Chainstay	406	406	408	408	409	409	411
Head tube	90	102	119	138	156	175	193

GEARING

	39	**53**
11	94	127
12	86	117
13	79	108
14	74	100
15	69	93
16	64	88
17	61	82
19	54	74
21	49	67
23	45	61

LeMond Victoire *3484000*14.093*

FRAMESET

Main tubes	Reynolds butted 3/2.5 Ti/OCLV 110	
Stays	Reynolds butted 3/2.5 Ti/OCLV 110	
Color	Titanium/Carbon Cloth • White/Black decal • Black fade-to-carbon fork	
Fork	Bontrager Race X Lite	371 mm axle-crown length
Headset	Cane Creek S-2 Aheadset, alloy	25.4/34.0/30.0, 26.5 mm stack height

CONTROLS

Handlebar	3TTT Forgie XL	31.8 mm clamp diameter
Stem	3TTT Forgie XL	41.0 mm steerer clamp height
Shift levers	Shimano Ultegra STI, Flite Deck compatible	
Brake levers	Integrated brake/shift	
Tape	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano Ultegra	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur	Shimano Ultegra	
Crankset	Shimano Ultegra 53/39	130 mm bolt hole circle
Bottom bracket	Shimano Ultegra	68 x 109.5 (shell x axle, mm), Shimano splined axle
Chain	Shimano HG-93	9 speed, 108 links
Cassette	Shimano Ultegra 12-25, 9spd	

WHEELSET

Front wheel	Bontrager Race Lite Road, 20˚ 279 mm radial spokes, Velox 16mm rim strip	592mm E.R.D.
Rear wheel	Bontrager Race Lite Road, 24˚ 291/291 mm 2x rear spokes, Velox 16mm rim strip	595 mm E.R.D.
Spokes	DT New Aero, ProLock alloy nipples	
Front tire	Bontrager Race X Lite, folding	700 x 23c
Rear tire	Bontrager Race X Lite, folding	700 x 23c
Inner tubes	Presta valve	

OTHER

Seatpost	LeMond, alloy micro-adjust	27.2 mm outer diameter
Saddle	SSM Era Luxe, CrMo rails	
Seatpost binder	Alloy w/integral bolt	35.0 mm inner diameter
Brakes	Shimano Ultegra	
Pedals	-not supplied-	9/16” axle
Additionals	2 water bottle mounts (1 bottle on 49), pump peg (not on 49, 51, 53)	
Bike weight	18.4 lb/8.35 kg	

FIT *dimensions in MM, unless specified*

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		67.0	68.5	70.6	72.3	73.6	75.3	77.4
	cm	170	174	179	184	187	191	196
Handlebar	width	420	440	440	460	460	460	460
Stem	length	90	100	110	110	120	120	130
	angle	10	10	10	10	10	10	10
Headset spacers		40	40	40	40	40	40	40
Crank	length	170	172.5	172.5	175	175	175	175
Seatpost	length	250	250	250	250	250	250	250
Steerer	length	193.5	205.5	222.5	241.5	259.5	278.0	296.0

GEOMETRY *dimensions in MM, unless specified*

Head tube angle	72.0	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	63	60	57	59	59	56	56
Seat tube angle	74.0	73.8	73.3	73.0	72.5	72.5	72.0
Effective top tube	525	532	545	565	575	591	606
Seat tube	488	498	512	528	542	560	573
Standover	728	741	754	772	785	803	815
Wheelbase	968	969	975	984	989	1000	1011
Bottom bracket height	264	266	266	269	269	269	269
Chainstay	406	406	408	408	409	409	411
Head tube	90	102	119	138	156	175	193

GEARING

	39	**53**
12	86	117
13	79	108
14	74	100
15	69	93
17	61	82
19	54	74
21	49	67
23	45	61
25	41	56

LeMond Victoire T *3485000*14.093*

FRAMESET

Main tubes	Reynolds butted 3/2.5 Ti/OCLV 110	
Stays	Reynolds butted 3/2.5 Ti/OCLV 110	
Color	Titanium/Carbon Cloth • White/Black decal • Black fade-to-carbon fork	
Fork	Bontrager Race X Lite	371 mm axle-crown length
Headset	Cane Creek S-2 Aheadset, alloy	25.4/34.0/30.0, 26.5 mm stack height

CONTROLS

Handlebar	3TTT Forgie XL	31.8 mm clamp diameter
Stem	3TTT Forgie XL	41.0 mm steerer clamp height
Shift levers	Shimano Ultegra STI, Flite Deck compatible	
Brake levers	Integrated brake/shift	
Tape	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano Ultegra T	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur	Shimano Ultegra GS	
Crankset	Shimano Ultegra 52/42/30	74/130 mm bolt hole circle
Bottom bracket	Shimano Ultegra	68 x 118 (shell x axle, mm), Shimano splined axle
Chain	Shimano HG-93	9 speed, 108 links
Cassette	Shimano Ultegra 12-25, 9spd	

WHEELSET

Front wheel	Bontrager Race Lite Road, 20°	592mm E.R.D.
	279 mm radial spokes, Velox 16mm rim strip	
Rear wheel	Bontrager Race Lite Road, 24°	595 mm E.R.D.
	291/291 mm 2x rear spokes, Velox 16mm rim strip	
Spokes	DT New Aero, ProLock alloy nipples	
Front tire	Bontrager Race X Lite, folding	700 x 23c
Rear tire	Bontrager Race X Lite, folding	700 x 23c
Inner tubes	Presta valve	

OTHER

Seatpost	LeMond, alloy micro-adjust	27.2 mm outer diameter
Saddle	SSM Era Luxe, CrMo rails	
Seatpost binder	Alloy w/integral bolt	35.0 mm inner diameter
Brakes	Shimano Ultegra	
Pedals	-not supplied-	9/16" axle
Additionals	2 water bottle mounts (1 bottle on 49), pump peg (not on 49, 51, 53)	
Bike weight	18.7 lb/8.49 kg	

FIT *dimensions in MM, unless specified*

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		67.0	68.5	70.6	72.3	73.6	75.3	77.4
	cm	170	174	179	184	187	191	196
Handlebar	width	420	440	440	460	460	460	460
Stem	length	90	100	110	110	120	120	130
	angle	10	10	10	10	10	10	10
Headset spacers		40	40	40	40	40	40	40
Crank	length	170	172.5	172.5	175	175	175	175
Seatpost	length	250	250	250	250	250	250	250
Steerer	length	193.5	205.5	222.5	241.5	259.5	278.0	296.0

GEOMETRY *dimensions in MM, unless specified*

Head tube angle	72.0	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	63	60	57	59	59	56	56
Seat tube angle	74.0	73.8	73.3	73.0	72.5	72.5	72.0
Effective top tube	525	532	545	565	575	591	606
Seat tube	488	498	512	528	542	560	573
Standover	728	741	754	772	785	803	815
Wheelbase	968	969	975	984	989	1000	1011
Bottom bracket height	264	266	266	269	269	269	269
Chainstay	406	406	408	408	409	409	411
Head tube	90	102	119	138	156	175	193

GEARING

	30	42	52
12	66	93	115
13	61	85	106
14	57	79	98
15	53	74	92
17	47	65	81
19	42	58	72
21	38	53	66
23	35	48	60
25	32	44	55

LeMond Arrivee *3482000*14.073*

FRAMESET

Main tubes	LeMond 3/2.5 titanium	
Stays	Reynolds titanium, tapered	
Color	Raw Titanium • Blue decal • Black fade-to-carbon fork	
Fork	Bontrager Race	370.0 mm axle-crown length
Headset	Cane Creek S-1	25.4/34.0/30.0, 30.1 mm stack height

CONTROLS

Handlebar	3TTT The	26.0 mm clamp diameter
Stem	3TTT The	40.0 mm steerer clamp height
Shift levers	Shimano Ultegra STI, Flite Deck compatible	
Brake levers	Integrated brake/shift	
Tape	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano 105	Down pull, 31.8 mm/ 1 1/4" attachment
Rear derailleur	Shimano Ultegra	
Crankset	Shimano Ultegra 53/39	130 mm bolt hole circle
Bottom bracket	Shimano Ultegra	68 x 109.5 (shell x axle, mm), Shimano splined axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	Shimano HG70 12-25, 9spd	

WHEELSET

Front wheel	Bontrager Select Road, 20°	593mm E.R.D.
	281 mm radial spokes, Velox 16mm rim strip	
Rear wheel	Bontrager Select Road, 24°	603 mm E.R.D.
	293/294 mm 2x rear spokes, Velox 16mm rim strip	
Spokes	DT 14g, ProLock brass nipples	
Front tire	Bontrager Race Lite	700 x 25c
Rear tire	Bontrager Race Lite	700 x 25c
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	LeMond, alloy micro-adjust	27.2 mm outer diameter
Saddle	SSM Era Luxe, CrMo/leather	
Seatpost binder	Alloy w/integral bolt	31.9 mm inner diameter
Brakes	Shimano Ultegra	
Pedals	-not supplied-	9/16" axle
Additionals	2 water bottle mounts (1 bottle on 49), pump peg (not on 49, 51)	
Bike weight	18.9 lb/8.58 kg	

FIT *dimensions in MM, unless specified*

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		65.3	68.6	69.3	72.0	72.8	75.4	78.0
	cm	166	174	176	183	185	192	198
Handlebar	width	420	440	440	460	460	460	460
Stem	length	80	100	100	110	110	120	135
	angle	12	12	12	12	12	12	12
Headset spacers		40	40	40	40	40	40	40
Crank	length	170	172.5	172.5	175	175	175	175
Seatpost	length	250	250	250	250	250	250	250
Steerer	length	191.1	206.1	222.1	238.6	257.1	281.1	301.1

GEOMETRY *dimensions in MM, unless specified*

Head tube angle	72.5	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	60	60	57	59	59	56	56
Seat tube angle	74.0	73.8	73.3	73.0	72.5	72.5	72.0
Effective top tube	519	532	545	565	576	591	606
Seat tube	528	545	565	584	604	626	648
Standover	751	767	784	802	820	845	864
Wheelbase	963	976	980	988	993	1007	1016
Bottom bracket height	266	266	266	266	266	270	270
Chainstay	410	413	413	413	413	416	416
Head tube	85	100	116	133	151	175	195

GEARING

	39	**53**
12	86	117
13	79	108
14	74	100
15	69	93
17	61	82
19	54	74
21	49	67
23	45	61
25	41	56

LeMond Arrivee T *3483000*14.073*

FRAMESET

Main tubes	LeMond 3/2.5 titanium	
Stays	Reynolds titanium, tapered	
Color	Raw Titanium • Blue decal • Black fade-to-carbon fork	
Fork	Bontrager Race	370.0 mm axle-crown length
Headset	Cane Creek S-1	25.4/34.0/30.0, 30.1 mm stack height

CONTROLS

Handlebar	3TTT The	26.0 mm clamp diameter
Stem	3TTT The	40.0 mm steerer clamp height
Shift levers	Shimano Ultegra STI, Flite Deck compatible	
Brake levers	Integrated brake/shift	
Tape	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano 105 T	Down pull, 31.8 mm/ 1 1/4" attachment
Rear derailleur	Shimano Ultegra GS	
Crankset	Shimano Ultegra 52/42/30	74/130 mm bolt hole circle
Bottom bracket	Shimano Ultegra	68 x 118 (shell x axle, mm), Shimano splined axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	Shimano HG70 12-25, 9spd	

WHEELSET

Front wheel	Bontrager Select Road, 20°	593mm E.R.D.
	281 mm radial spokes, Velox 16mm rim strip	
Rear wheel	Bontrager Select Road, 24°	603 mm E.R.D.
	293/294 mm 2x rear spokes, Velox 16mm rim strip	
Spokes	DT 14g, ProLock brass nipples	
Front tire	Bontrager Race Lite	700 x 25c
Rear tire	Bontrager Race Lite	700 x 25c
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	LeMond, alloy micro-adjust	27.2 mm outer diameter
Saddle	SSM Era Luxe, CrMo/leather	
Seatpost binder	Alloy w/integral bolt	31.9 mm inner diameter
Brakes	Shimano Ultegra	
Pedals	-not supplied-	9/16" axle
Additionals	2 water bottle mounts (1 bottle on 49), pump peg (not on 49, 51)	

FIT *dimensions in MM, unless specified*

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		65.3	68.6	69.3	72.0	72.8	75.4	78.0
	cm	166	174	176	183	185	192	198
Handlebar	width	420	440	440	460	460	460	460
Stem	length	80	100	100	110	110	120	135
	angle	12	12	12	12	12	12	12
Headset spacers		40	40	40	40	40	40	40
Crank	length	170	172.5	172.5	175	175	175	175
Seatpost	length	250	250	250	250	250	250	250
Steerer	length	191.1	206.1	222.1	238.6	257.1	281.1	301.1

GEOMETRY *dimensions in MM, unless specified*

Head tube angle	72.5	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	60	60	57	59	59	56	56
Seat tube angle	74.0	73.8	73.3	73.0	72.5	72.5	72.0
Effective top tube	519	532	545	565	576	591	606
Seat tube	528	545	565	584	604	626	648
Standover	751	767	784	802	820	845	864
Wheelbase	963	976	980	988	993	1007	1016
Bottom bracket height	266	266	266	266	266	270	270
Chainstay	410	413	413	413	413	416	416
Head tube	85	100	116	133	151	175	195

GEARING

	30	42	52
12	66	93	115
13	61	85	106
14	57	79	98
15	53	74	92
17	47	65	81
19	42	58	72
21	38	53	66
23	35	48	60
25	32	44	55

LeMond Maillot Jaune *3478000*14.093*

FRAMESET

Main tubes	True Temper OX Platinum /OCLV 120	
Stays	True Temper OX Platinum/OCLV 120	
Color	Red/Carbon Cloth • Red decal • Black fade-to-carbon fork	
Fork	Bontrager Race X Lite	371 mm axle-crown length
Headset	Cane Creek S-6 Aheadset, alloy	25.4/34.0/30.0, 27.1 mm stack height

CONTROLS

Handlebar	3TTT Forgie XL	31.8 mm clamp diameter
Stem	3TTT Forgie XL	41.0 mm steerer clamp height
Shift levers	Shimano Ultegra STI, Flite Deck compatible	
Brake levers	Integrated brake/shift	
Tape	Powercork	

DRIVETRAIN

Front derailleur	Shimano Dura-Ace	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur	Shimano Dura-Ace	
Crankset	Shimano Dura-Ace 53/39	130 mm bolt hole circle
Bottom bracket	Shimano Dura-Ace, integral axle	Integral axle
Chain	Shimano Dura-Ace	10 speed, 108 links
Cassette	Shimano Dura-Ace 11-23, 10spd	

WHEELSET

Front wheel	Bontrager Race Lite Road, 20° 279 mm radial spokes, Velox 16mm rim strip	592mm E.R.D.
Rear wheel	Bontrager Race Lite Road, 24° 291/291 mm 2x rear spokes, Velox 16mm rim strip	595 mm E.R.D.
Spokes	DT New Aero, ProLock alloy nipples	
Front tire	Bontrager Race X Lite, folding	700 x 23c
Rear tire	Bontrager Race X Lite, folding	700 x 23c
Inner tubes	Presta valve	

OTHER

Seatpost	LeMond, alloy micro-adjust	27.2 mm outer diameter
Saddle	SSM Era Luxe, CrMo/leather	
Seatpost binder	Alloy w/integral bolt	35.0 mm inner diameter
Brakes	Shimano Dura-Ace	
Pedals	-not supplied-	9/16" axle
Additionals	2 water bottle mounts (1 bottle on 49), pump peg (not on 49, 51, 53)	
Bike weight	18.0 lb/8.17 kg	

FIT *dimensions in MM, unless specified*

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		67.2	68.7	70.4	72.1	73.8	75.5	77.6
	cm	171	175	179	183	187	192	197
Handlebar	width	420	440	440	460	46 0	460	460
Stem	length	90	100	110	110	120	120	130
	angle	10	10	10	10	10	10	10
Headset spacers		30	30	30	30	30	30	30
Crank	length	170	172.5	172.5	175	175	175	175
Seatpost	length	330	330	330	330	330	330	330
Steerer	length	199.1	211.1	228.1	247.1	265.1	284.1	304.1

GEOMETRY *dimensions in MM, unless specified*

Head tube angle	72.0	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	63	60	57	59	59	56	56
Seat tube angle	74.0	73.8	73.3	73.0	72.5	72.5	72.0
Effective top tube	525	532	545	565	575	591	606
Seat tube	488	498	512	528	542	560	574
Standover	728	741	754	772	785	803	815
Wheelbase	968	970	975	984	989	999	1010
Bottom bracket height	264	266	266	269	269	269	269
Chainstay	406	406	408	408	409	409	411
Head tube	105	117	134	153	171	190	210

GEARING

	39	**53**
11	94	127
12	86	117
13	79	108
14	74	100
15	69	93
16	64	88
17	61	82
19	54	74
21	49	67
23	45	61

LeMond Zurich *3446000*14.083*

FRAMESET

Main tubes	True Temper OX Platinum/OCLV 120	
Stays	True Temper OX Platinum/OCLV 120	
Color	Metallic Blue/Carbon Cloth • Blue decal • Black fade-to-carbon fork	
Fork	Bontrager Race Lite	371 mm axle-crown length
Headset	Cane Creek C-2 Aheadset, alloy	25.4/34.0/30.0, 26.5 mm stack height

CONTROLS

Handlebar	3TTT Forgie XL	31.8 mm clamp diameter
Stem	3TTT Forgie XL	41.0 mm steerer clamp height
Shift levers	Shimano Ultegra STI, Flite Deck compatible	
Brake levers	Integrated brake/shift	
Tape	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano Ultegra	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur	Shimano Ultegra	
Crankset	Shimano Ultegra 53/39	130 mm bolt hole circle
Bottom bracket	Shimano Ultegra	68 x 109.5 (shell x axle, mm), Shimano splined axle
Chain	Shimano HG-93	9 speed, 108 links
Cassette	Shimano Ultegra 12-25, 9spd	

WHEELSET

Front wheel	Bontrager Race Road, 20°	592mm E.R.D.
	279 mm radial spokes, Velox 16mm rim strip	
Rear wheel	Bontrager Race Road, 24°	595 mm E.R.D.
	291/291 mm 2x rear spokes, Velox 16mm rim strip	
Spokes	DT 14g, ProLock brass nipples	
Front tire	Bontrager Race X Lite, folding	700 x 23c
Rear tire	Bontrager Race X Lite, folding	700 x 23c
Inner tubes	Presta valve	

OTHER

Seatpost	LeMond, alloy micro-adjust	27.2 mm outer diameter
Saddle	SSM Era Luxe, CrMo/leather	
Seatpost binder	Alloy w/integral bolt	35.0 mm inner diameter
Brakes	Shimano Ultegra	
Pedals	-not supplied-	9/16" axle
Additionals	2 water bottle mounts (1 bottle on 49), pump peg (not on 49, 51, 53)	
Bike weight	19.2 lb/8.72 kg	

FIT *dimensions in MM, unless specified*

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		67.2	68.7	70.3	72.1	73.7	75.5	77.5
	cm	171	175	179	183	187	192	197
Handlebar	width	420	440	440	460	46 0	460	460
Stem	length	90	100	110	110	120	120	130
	angle	10	10	10	10	10	10	10
Headset spacers		30	30	30	30	30	30	30
Crank	length	170	172.5	172.5	175	175	175	175
Seatpost	length	330	330	330	330	330	330	330
Steerer	length	198.5	210.5	227.5	246.5	264.5	283.5	303.5

GEOMETRY *dimensions in MM, unless specified*

Head tube angle	72.0	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	63	60	57	59	59	56	56
Seat tube angle	74.0	73.8	73.3	73.0	72.5	72.5	72.0
Effective top tube	525	532	545	565	575	591	606
Seat tube	488	498	512	528	542	560	574
Standover	728	741	754	772	785	803	815
Wheelbase	968	970	975	984	989	999	1010
Bottom bracket height	264	266	266	269	269	269	269
Chainstay	406	406	408	408	409	409	411
Head tube	105	117	134	153	171	190	210

GEARING

	39	**53**
12	86	117
13	79	108
14	74	100
15	69	93
17	61	82
19	54	74
21	49	67
23	45	61
25	41	56

LeMond Zurich T *3447000*14.083*

FRAMESET

Main tubes	True Temper OX Platinum/OCLV 120	
Stays	True Temper OX Platinum/OCLV 120	
Color	Metallic Blue/Carbon Cloth • Blue decal • Black fade-to-carbon fork	
Fork	Bontrager Race Lite	371 mm axle-crown length
Headset	Cane Creek C-2 Aheadset, alloy	25.4/34.0/30.0, 26.5 mm stack height

CONTROLS

Handlebar	3TTT Forgie XL	31.8 mm clamp diameter
Stem	3TTT Forgie XL	41.0 mm steerer clamp height
Shift levers	Shimano Ultegra STI, Flite Deck compatible	
Brake levers	Integrated brake/shift	
Tape	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano Ultegra T	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur	Shimano Ultegra GS	
Crankset	Shimano Ultegra 52/42/30	74/130 mm bolt hole circle
Bottom bracket	Shimano Ultegra	68 x 118 (shell x axle, mm), Shimano splined axle
Chain	Shimano HG-93	9 speed, 108 links
Cassette	Shimano Ultegra 12-25, 9spd	

WHEELSET

Front wheel	Bontrager Race Road, 20°	592mm E.R.D.
	279 mm radial spokes, Velox 16mm rim strip	
Rear wheel	Bontrager Race Road, 24°	595 mm E.R.D.
	291/291 mm 2x rear spokes, Velox 16mm rim strip	
Spokes	DT 14g, ProLock brass nipples	
Front tire	Bontrager Race X Lite, folding	700 x 23c
Rear tire	Bontrager Race X Lite, folding	700 x 23c
Inner tubes	Presta valve	

OTHER

Seatpost	LeMond, alloy micro-adjust	27.2 mm outer diameter
Saddle	SSM Era Luxe, CrMo/leather	
Seatpost binder	Alloy w/integral bolt	35.0 mm inner diameter
Brakes	Shimano Ultegra	
Pedals	-not supplied-	9/16” axle
Additionals	2 water bottle mounts (1 bottle on 49), pump peg (not on 49, 51, 53)	
Bike weight	19.3 lb/8.76 kg	

FIT *dimensions in MM, unless specified*

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		67.2	68.7	70.3	72.1	73.7	75.5	77.5
	cm	171	175	179	183	187	192	197
Handlebar	width	420	440	440	460	46 0	460	460
Stem	length	90	100	110	110	120	120	130
	angle	10	10	10	10	10	10	10
Headset spacers		30	30	30	30	30	30	30
Crank	length	170	172.5	172.5	175	175	175	175
Seatpost	length	330	330	330	330	330	330	330
Steerer	length	198.5	210.5	227.5	246.5	264.5	283.5	303.5

GEOMETRY *dimensions in MM, unless specified*

Head tube angle	72.0	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	63	60	57	59	59	56	56
Seat tube angle	74.0	73.8	73.3	73.0	72.5	72.5	72.0
Effective top tube	525	532	545	565	575	591	606
Seat tube	488	498	512	528	542	560	574
Standover	728	741	754	772	785	803	815
Wheelbase	968	970	975	984	989	999	1010
Bottom bracket height	264	266	266	269	269	269	269
Chainstay	406	406	408	408	409	409	411
Head tube	105	117	134	153	171	190	210

GEARING

	30	42	52
12	66	93	115
13	61	85	106
14	57	79	98
15	53	74	92
17	47	65	81
19	42	58	72
21	38	53	66
23	35	48	60
25	32	44	55

LeMond Zurich T women's *3447003*14.083*

FRAMESET

Main tubes	True Temper OX Platinum/OCLV 120	
Stays	True Temper OX Platinum/OCLV 120	
Color	Metallic Blue/Carbon Cloth • Blue/Warm Silver decal • Black fade-to-carbon fork	
Fork	Bontrager Race Lite	371 mm axle-crown length
Headset	Cane Creek C-2 Aheadset, alloy	25.4/34.0/30.0, 26.5 mm stack height

CONTROLS

Handlebar	3TTT Forgie XL	31.8 mm clamp diameter
Stem	3TTT Forgie XL	41.0 mm steerer clamp height
Shift levers	Shimano Ultegra STI, adjustable reach	
Brake levers	Integrated brake/shift	
Tape	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano Ultegra T	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur	Shimano Ultegra GS	
Crankset	Shimano Ultegra 52/42/30	74/130 mm bolt hole circle
Bottom bracket	Shimano Ultegra	68 x 118 (shell x axle, mm), Shimano splined axle
Chain	Shimano HG-93	9 speed, 108 links
Cassette	Shimano Ultegra 12-25, 9spd	

WHEELSET

Front wheel	Bontrager Race Road, 20°	592mm E.R.D.
	279 mm radial spokes, Velox 16mm rim strip	
Rear wheel	Bontrager Race Road, 24°	595 mm E.R.D.
	291/291 mm 2x rear spokes, Velox 16mm rim strip	
Spokes	DT 14g, ProLock brass nipples	
Front tire	Bontrager Race X Lite, folding	700 x 23c
Rear tire	Bontrager Race X Lite, folding	700 x 23c
Inner tubes	Presta valve	

OTHER

Seatpost	LeMond, alloy micro-adjust	27.2 mm outer diameter
Saddle	Oasis, women's, CrMo/leather	
Seatpost binder	Alloy w/integral bolt	35.0 mm inner diameter
Brakes	Shimano Ultegra	
Pedals	-not supplied-	9/16" axle
Additionals	2 water bottle mounts (1 bottle on 49), pump peg (not on 49, 51, 53)	
Bike weight	19.2 lb/8.72 kg	

FIT *dimensions in MM, unless specified*

Frame	Size	49	53
Rider height, in.		65.6	68.2
	cm	167	173
Handlebar	width	420	420
Stem	length	90	100
	angle	10	10
Headset spacers		30	30
Crank	length	165	170
Seatpost	length	330	330
Steerer	length	198.5	227.5

GEOMETRY *dimensions in MM, unless specified*

Head tube angle	71.3	72.0
Fork offset	45.0	45.0
Trail	68	63
Seat tube angle	74.0	73.3
Effective top tube	510	530
Seat tube	488	512
Standover	728	754
Wheelbase	960	970
Bottom bracket height	264	266
Chainstay	406	408
Head tube	105	134

GEARING

	30	**42**	**52**
12	66	93	115
13	61	85	106
14	57	79	98
15	53	74	92
17	47	65	81
19	42	58	72
21	38	53	66
23	35	48	60
25	32	44	55

LeMond Buenos Aires *3444000*14.083*

FRAMESET

Main tubes	True Temper OX Platinum/OCLV 120	
Stays	True Temper OX Platinum/OCLV 120	
Color	Silver/Carbon Cloth • White decal • Black fade-to-carbon fork	
Fork	Bontrager Race	371 mm axle-crown length
Headset	Cane Creek S-1	25.4/34.0/30.0, 30.1 mm stack height

CONTROLS

Handlebar	3TTT The	26.0 mm clamp diameter
Stem	3TTT The	40.0 mm steerer clamp height
Shift levers	Shimano Ultegra STI, Flite Deck compatible	
Brake levers	Integrated brake/shift	
Tape	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano 105	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur	Shimano Ultegra	
Crankset	Shimano Ultegra 53/39	130 mm bolt hole circle
Bottom bracket	Shimano 105	68 x 109.5 (shell x axle, mm), Shimano splined axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	Shimano HG70 12-25, 9spd	

WHEELSET

Front wheel	Bontrager Select Road, 20°	593mm E.R.D.
	281 mm radial spokes, Velox 16mm rim strip	
Rear wheel	Bontrager Select Road, 24°	603 mm E.R.D.
	293/294 mm 2x rear spokes, Velox 16mm rim strip	
Spokes	DT 14g, ProLock brass nipples	
Front tire	Bontrager Race Lite, folding	700 x 23c
Rear tire	Bontrager Race Lite, folding	700 x 23c
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	LeMond, alloy micro-adjust	27.2 mm outer diameter
Saddle	CRZ+ Road, Cro-Moly rails	
Seatpost binder	Alloy w/integral bolt	35.0 mm inner diameter
Brakes	Shimano 105	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additionals	2 water bottle mounts (1 bottle on 49), pump peg (not on 49, 51, 53)	
Bike weight	20.5 lb/9.31 kg	

FIT *dimensions in MM, unless specified*

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		66.1	68.5	70.5	72.2	73.9	75.7	78.0
	cm	168	174	179	183	188	192	198
Handlebar	width	420	440	440	460	46 0	460	460
Stem	length	80	100	110	110	120	120	135
	angle	12	12	12	12	12	12	12
Headset spacers		30	30	30	30	30	30	25
Crank	length	170	172.5	172.5	175	175	175	175
Seatpost	length	330	330	330	330	330	330	330
Steerer	length	201.1	213.1	230.1	249.1	267.1	286.1	301.1

GEOMETRY *dimensions in MM, unless specified*

Head tube angle	72.0	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	63	60	57	59	59	56	56
Seat tube angle	74.0	73.8	73.3	73.0	72.5	72.5	72.0
Effective top tube	525	532	545	565	575	591	606
Seat tube	488	498	512	528	542	560	574
Standover	728	741	754	772	785	803	815
Wheelbase	968	970	975	984	989	999	1010
Bottom bracket height	264	266	266	269	269	269	269
Chainstay	406	406	408	408	409	409	411
Head tube	105	117	134	153	171	190	210

GEARING

	39	**53**
12	86	117
13	79	108
14	74	100
15	69	93
17	61	82
19	54	74
21	49	67
23	45	61
25	41	56

LeMond Buenos Aires T *3445000*14.083*

FRAMESET

Main tubes	True Temper OX Platinum/OCLV 120	
Stays	True Temper OX Platinum/OCLV 120	
Color	Silver/Carbon Cloth • White decal • Black fade-to-carbon fork	
Fork	Bontrager Race	371 mm axle-crown length
Headset	Cane Creek S-1	25.4/34.0/30.0, 30.1 mm stack height

CONTROLS

Handlebar	3TTT The	26.0 mm clamp diameter
Stem	3TTT The	40.0 mm steerer clamp height
Shift levers	Shimano Ultegra STI, Flite Deck compatible	
Brake levers	Integrated brake/shift	
Tape	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano 105 T	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur	Shimano Ultegra GS	
Crankset	Shimano Ultegra 52/42/30	74/130 mm bolt hole circle
Bottom bracket	Shimano 105	68 x 118 (shell x axle, mm), Shimano splined axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	Shimano HG70 12-25, 9spd	

WHEELSET

Front wheel	Bontrager Select Road, 20°	593mm E.R.D.
	281 mm radial spokes, Velox 16mm rim strip	
Rear wheel	Bontrager Select Road, 24°	603 mm E.R.D.
	293/294 mm 2x rear spokes, Velox 16mm rim strip	
Spokes	DT 14g, ProLock brass nipples	
Front tire	Bontrager Race Lite, folding	700 x 23c
Rear tire	Bontrager Race Lite, folding	700 x 23c
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	LeMond, alloy micro-adjust	27.2 mm outer diameter
Saddle	CRZ+ Road, Cro-Moly rails	
Seatpost binder	Alloy w/integral bolt	35.0 mm inner diameter
Brakes	Shimano 105	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additionals	2 water bottle mounts (1 bottle on 49), pump peg (not on 49, 51, 53)	
Bike weight	20.9 lb/9.49 kg	

FIT *dimensions in MM, unless specified*

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		66.1	68.5	70.5	72.2	73.9	75.7	78.0
	cm	168	174	179	183	188	192	198
Handlebar	width	420	440	440	460	46 0	460	460
Stem	length	80	100	110	110	120	120	135
	angle	12	12	12	12	12	12	12
Headset spacers		30	30	30	30	30	30	25
Crank	length	170	172.5	172.5	175	175	175	175
Seatpost	length	330	330	330	330	330	330	330
Steerer	length	201.1	213.1	230.1	249.1	267.1	286.1	301.1

GEOMETRY *dimensions in MM, unless specified*

Head tube angle	72.0	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	63	60	57	59	59	56	56
Seat tube angle	74.0	73.8	73.3	73.0	72.5	72.5	72.0
Effective top tube	525	532	545	565	575	591	606
Seat tube	488	498	512	528	542	560	574
Standover	728	741	754	772	785	803	815
Wheelbase	968	970	975	984	989	999	1010
Bottom bracket height	264	266	266	269	269	269	269
Chainstay	406	406	408	408	409	409	411
Head tube	105	117	134	153	171	190	210

GEARING

	30	42	52
12	66	93	115
13	61	85	106
14	57	79	98
15	53	74	92
17	47	65	81
19	42	58	72
21	38	53	66
23	35	48	60
25	32	44	55

LeMond Alpe d'Huez *3442000*14.083*

FRAMESET

Main tubes	6066 T6 aluminum, fully butted	
Stays	6066 T6 aluminum, fully butted	
Color	Brushed Aluminum/Red • White/Warm Silver decal • Black fade-to-carbon fork	
Fork	Bontrager Race	371 mm axle-crown length
Headset	Cane Creek S-1	25.4/34.0/30.0, 30.1 mm stack height

CONTROLS

Handlebar	3TTT The	26.0 mm clamp diameter
Stem	3TTT The	40.0 mm steerer clamp height
Shift levers	Shimano Ultegra STI, Flite Deck compatible	
Brake levers	Integrated brake/shift	
Tape	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano 105	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur	Shimano Ultegra	
Crankset	Shimano Ultegra 53/39	130 mm bolt hole circle
Bottom bracket	Shimano 105	68 x 109.5 (shell x axle, mm), Shimano splined axle
Chain	Shimano HG-73	9 speed, 108 links
Cassette	Shimano HG50 12-25, 9spd	

WHEELSET

Front wheel	Bontrager Select Road, 20°	593mm E.R.D.
	281 mm radial spokes, Velox 16mm rim strip	
Rear wheel	Bontrager Select Road, 24°	603 mm E.R.D.
	293/294 mm 2x rear spokes, Velox 16mm rim strip	
Spokes	DT 14g, ProLock brass nipples	
Front tire	Bontrager Race Lite, folding	700 x 25c
Rear tire	Bontrager Race Lite, folding	700 x 25c
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	LeMond, alloy micro-adjust	27.2 mm outer diameter
Saddle	CRZ+ Road, Cro-Moly rails	
Seatpost binder	Alloy w/integral bolt	31.9 mm inner diameter
Brakes	Shimano Ultegra	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additionals	2 water bottle mounts (1 bottle on 49), pump peg (not on 49, 51)	
Bike weight	19.8 lb/8.99 kg	

FIT *dimensions in MM, unless specified*

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		66.1	68.5	70.5	72.2	73.9	75.7	78.2
	cm	168	174	179	183	188	192	199
Handlebar	width	420	440	440	460	46 0	460	460
Stem	length	80	100	110	110	120	120	135
	angle	12	12	12	12	12	12	12
Headset spacers		30	30	30	30	30	30	30
Crank	length	170	172.5	172.5	175	175	175	175
Seatpost	length	330	330	330	330	330	330	330
Steerer	length	201.1	213.1	230.1	249.1	267.1	286.1	306.1

GEOMETRY *dimensions in MM, unless specified*

Head tube angle	72.0	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	63	60	57	59	59	56	56
Seat tube angle	74.0	73.8	73.3	73.0	72.5	72.5	72.0
Effective top tube	525	532	545	565	575	591	606
Seat tube	488	498	512	528	542	560	574
Standover	728	741	754	772	785	803	815
Wheelbase	972	974	980	989	993	1007	1015
Bottom bracket height	264	266	266	269	269	269	269
Chainstay	410	410	413	413	413	416	416
Head tube	105	117	134	153	171	190	210

GEARING

	39	**53**
12	86	117
13	79	108
14	74	100
15	69	93
17	61	82
19	54	74
21	49	67
23	45	61
25	41	56

LeMond Alpe d'Huez T *3443000*14.083*

FRAMESET

Main tubes	6066 T6 aluminum, fully butted	
Stays	6066 T6 aluminum, fully butted	
Color	Brushed Aluminum/Red • White/Warm Silver decal • Black fade-to-carbon fork	
Fork	Bontrager Race	371 mm axle-crown length
Headset	Cane Creek S-1	25.4/34.0/30.0, 30.1 mm stack height

CONTROLS

Handlebar	3TTT The	26.0 mm clamp diameter
Stem	3TTT The	40.0 mm steerer clamp height
Shift levers	Shimano Ultegra STI, Flite Deck compatible	
Brake levers	Integrated brake/shift	
Tape	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano 105 T	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur	Shimano Ultegra GS	
Crankset	Shimano Ultegra 52/42/30	74/130 mm bolt hole circle
Bottom bracket	Shimano 105	68 x 118 (shell x axle, mm), Shimano splined axle
Chain	Shimano HG-73	9 speed, 108 links
Cassette	Shimano HG50 12-25, 9spd	

WHEELSET

Front wheel	Bontrager Select Road, 20°	593mm E.R.D.
	281 mm radial spokes, Velox 16mm rim strip	
Rear wheel	Bontrager Select Road, 24°	603 mm E.R.D.
	293/294 mm 2x rear spokes, Velox 16mm rim strip	
Spokes	DT 14g, ProLock brass nipples	
Front tire	Bontrager Race Lite, folding	700 x 25c
Rear tire	Bontrager Race Lite, folding	700 x 25c
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	LeMond, alloy micro-adjust	27.2 mm outer diameter
Saddle	CRZ+ Road, Cro-Moly rails	
Seatpost binder	Alloy w/integral bolt	31.9 mm inner diameter
Brakes	Shimano Ultegra	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additionals	2 water bottle mounts (1 bottle on 49), pump peg (not on 49, 51)	
Bike weight	20.2 lb/9.17 kg	

FIT *dimensions in MM, unless specified*

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		66.1	68.5	70.5	72.2	73.9	75.7	78.2
	cm	168	174	179	183	188	192	199
Handlebar	width	420	440	440	460	46 0	460	460
Stem	length	80	100	110	110	120	120	135
	angle	12	12	12	12	12	12	12
Headset spacers		30	30	30	30	30	30	30
Crank	length	170	172.5	172.5	175	175	175	175
Seatpost	length	330	330	330	330	330	330	330
Steerer	length	201.1	213.1	230.1	249.1	267.1	286.1	306.1

GEOMETRY *dimensions in MM, unless specified*

Head tube angle	72.0	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	63	60	57	59	59	56	56
Seat tube angle	74.0	73.8	73.3	73.0	72.5	72.5	72.0
Effective top tube	525	532	545	565	575	591	606
Seat tube	488	498	512	528	542	560	574
Standover	728	741	754	772	785	803	815
Wheelbase	972	974	980	989	993	1007	1015
Bottom bracket height	264	266	266	269	269	269	269
Chainstay	410	410	413	413	413	416	416
Head tube	105	117	134	153	171	190	210

GEARING

	30	42	52
12	66	93	115
13	61	85	106
14	57	79	98
15	53	74	92
17	47	65	81
19	42	58	72
21	38	53	66
23	35	48	60
25	32	44	55

LeMond Tourmalet *3428000*14.083*

FRAMESET

Main tubes	6066 T6 aluminum, fully butted	
Stays	6066 T6 aluminum, fully butted	
Color	Brushed Aluminum/Green • White/Green decal • Black fade to carbon fork	
Fork	Bontrager Race	371 mm axle-crown length
Headset	Slimstack	25.4/34.0/30.0, 36.3 mm stack height

CONTROLS

Handlebar	3TTT The	26.0 mm clamp diameter
Stem	3TTT The	40.0 mm steerer clamp height
Shift levers	Shimano 105 STI, Flite Deck compatible	
Brake levers	Integrated brake/shift	
Tape	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano 105	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur	Shimano Ultegra	
Crankset	Shimano 105 53/39	130 mm bolt hole circle
Bottom bracket	Shimano 105	68 x 110 (shell x axle, mm), Shimano splined axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	Shimano HG50 12-25, 9spd	

WHEELSET

Front wheel	Bontrager Select Road, 20°	593mm E.R.D.
	281 mm radial spokes, Velox 16mm rim strip	
Rear wheel	Bontrager Select Road, 24°	603 mm E.R.D.
	293/294 mm 2x rear spokes, Velox 16mm rim strip	
Spokes	DT 14g, ProLock brass nipples	
Front tire	Bontrager Race Lite	700 x 25c
Rear tire	Bontrager Race Lite	700 x 25c
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	LeMond, alloy micro-adjust	27.2 mm outer diameter
Saddle	CRZ+ Road	
Seatpost binder	Alloy w/integral bolt	31.9 mm inner diameter
Brakes	Alloy dual pivot	
Pedals	Alloy road, sealed, w/clips and straps	9/16" axle
Additionals	2 water bottle mounts (1 bottle on 49), pump peg (not on 49, 51)	
Bike weight	20.6 lb/9.35 kg	

FIT *dimensions in MM, unless specified*

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		66.1	68.8	70.5	72.2	73.9	75.6	78.1
	cm	168	175	179	183	188	192	198
Handlebar	width	420	440	440	460	46 0	460	460
Stem	length	80	100	110	110	120	120	135
	angle	12	12	12	12	12	12	12
Headset spacers		20	20	20	20	20	20	20
Crank	length	170	172.5	172.5	175	175	175	175
Seatpost	length	330	330	330	330	330	330	330
Steerer	length	197.3	209.3	226.3	245.3	263.3	282.3	302.3

GEOMETRY *dimensions in MM, unless specified*

Head tube angle	72.0	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	63	60	57	59	59	56	56
Seat tube angle	74.0	73.8	73.3	73.0	72.5	72.5	72.0
Effective top tube	525	532	545	565	575	591	606
Seat tube	488	498	512	528	542	560	574
Standover	728	741	754	772	785	803	815
Wheelbase	972	974	980	989	993	1007	1015
Bottom bracket height	264	266	266	269	269	269	269
Chainstay	410	410	413	413	413	416	416
Head tube	105	117	134	153	171	190	210

GEARING

	39	**53**
12	86	117
13	79	108
14	74	100
15	69	93
17	61	82
19	54	74
21	49	67
23	45	61
25	41	56

LeMond Tourmalet T *3429000*14.083*

FRAMESET

Main tubes	6066 T6 aluminum, fully butted	
Stays	6066 T6 aluminum, fully butted	
Color	Brushed Aluminum/Green • White/Green decal • Black fade to carbon fork	
Fork	Bontrager Race	371 mm axle-crown length
Headset	Slimstack	25.4/34.0/30.0, 36.3 mm stack height

CONTROLS

Handlebar	3TTT The	26.0 mm clamp diameter
Stem	3TTT The	40.0 mm steerer clamp height
Shift levers	Shimano 105 STI, Flite Deck compatible	
Brake levers	Integrated brake/shift	
Tape	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano 105	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur	Shimano Ultegra	
Crankset	Shimano 105 53/39	130 mm bolt hole circle
Bottom bracket	Shimano 105	68 x 110 (shell x axle, mm), Shimano splined axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	Shimano HG50 12-25, 9spd	

WHEELSET

Front wheel	Bontrager Select Road, 20°	593mm E.R.D.
	281 mm radial spokes, Velox 16mm rim strip	
Rear wheel	Bontrager Select Road, 24°	603 mm E.R.D.
	293/294 mm 2x rear spokes, Velox 16mm rim strip	
Spokes	DT 14g, ProLock brass nipples	
Front tire	Bontrager Race Lite	700 x 25c
Rear tire	Bontrager Race Lite	700 x 25c
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	LeMond, alloy micro-adjust	27.2 mm outer diameter
Saddle	CRZ+ Road	
Seatpost binder	Alloy w/integral bolt	31.9 mm inner diameter
Brakes	Alloy dual pivot	
Pedals	Alloy road, sealed, w/clips and straps	9/16" axle
Additionals	2 water bottle mounts (1 bottle on 49), pump peg (not on 49, 51)	

FIT *dimensions in MM, unless specified*

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		66.1	68.8	70.5	72.2	73.9	75.6	78.1
	cm	168	175	179	183	188	192	198
Handlebar	width	420	440	440	460	46 0	460	460
Stem	length	80	100	110	110	120	120	135
	angle	12	12	12	12	12	12	12
Headset spacers		20	20	20	20	20	20	20
Crank	length	170	172.5	172.5	175	175	175	175
Seatpost	length	330	330	330	330	330	330	330
Steerer	length	197.3	209.3	226.3	245.3	263.3	282.3	302.3

GEOMETRY *dimensions in MM, unless specified*

Head tube angle	72.0	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	63	60	57	59	59	56	56
Seat tube angle	74.0	73.8	73.3	73.0	72.5	72.5	72.0
Effective top tube	525	532	545	565	575	591	606
Seat tube	488	498	512	528	542	560	574
Standover	728	741	754	772	785	803	815
Wheelbase	972	974	980	989	993	1007	1015
Bottom bracket height	264	266	266	269	269	269	269
Chainstay	410	410	413	413	413	416	416
Head tube	105	117	134	153	171	190	210

GEARING

	39	**53**
12	86	117
13	79	108
14	74	100
15	69	93
17	61	82
19	54	74
21	49	67
23	45	61
25	41	56

LeMond Reno *3422000*14.083*

FRAMESET

Main tubes	6066 T6 aluminum, fully butted	
Stays	6066 T6 aluminum, fully butted	
Color	Metallic Black/Red • White/Black decal • Black fade to carbon fork	
Fork	Bontrager Race	371 mm axle-crown length
Headset	Slimstack	25.4/34.0/30.0, 36.3 mm stack height

CONTROLS

Handlebar	Alloy Ergo	26.0 mm clamp diameter
Stem	Alloy quick change, direct connect	40.0 mm steerer clamp height
Shift levers	Shimano Tiagra STI Dual Control	
Brake levers	Integrated brake/shift	
Tape	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano Tiagra	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur	Shimano 105	
Crankset	Shimano Tiagra 53/39	130 mm bolt hole circle
Bottom bracket	Shimano BB-UN40	68 x 110 (shell x axle, mm), Square axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	Shimano HG50 12-25, 9spd	

WHEELSET

Front wheel	Alloy, QR hub, 32°, Matrix Aurora rim 299 mm 3x spokes, Velox 16mm rim strip	610mm E.R.D.
Rear wheel	Alloy, QR hub, 32°, Matrix Aurora RDR rim 293/294 mm 3x rear spokes, Velox 16mm rim strip	603 mm E.R.D.
Spokes	14G stainless	
Front tire	Bontrager Race Lite	700 x 25c
Rear tire	Bontrager Race Lite	700 x 25c
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	LeMond, alloy micro-adjust	27.2 mm outer diameter
Saddle	CRZ+ Road	
Seatpost binder	Alloy w/integral bolt	31.9 mm inner diameter
Brakes	Alloy dual pivot	
Pedals	Alloy road, sealed, w/clips and straps	9/16" axle
Additionals	2 water bottle mounts (1 bottle on 49), pump peg (not on 49, 51)	
Bike weight	20.7 lb/9.40 kg	

FIT *dimensions in MM, unless specified*

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		66.9	68.5	70.5	72.3	74.0	75.7	77.8
	cm	170	174	179	184	188	192	198
Handlebar	width	400	420	420	440	440	440	460
Stem	length	90	100	110	110	120	120	130
	angle	17	17	17	17	17	17	17
Headset spacers		20	20	20	20	20	20	20
Crank	length	170	170	170	175	175	175	175
Seatpost	length	330	330	330	330	330	330	330
Steerer	length	197.3	209.3	226.3	245.3	263.3	282.3	302.3

GEOMETRY *dimensions in MM, unless specified*

	49	51	53	55	57	59	61
Head tube angle	72.0	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	63	60	57	59	59	56	56
Seat tube angle	74.0	73.8	73.3	73.0	72.5	72.5	72.0
Effective top tube	525	532	545	565	575	591	606
Seat tube	488	498	512	528	542	560	574
Standover	728	741	754	772	785	803	815
Wheelbase	972	974	980	989	993	1007	1015
Bottom bracket height	264	266	266	269	269	269	269
Chainstay	410	410	413	413	413	416	416
Head tube	105	117	134	153	171	190	210

GEARING

	39	**53**
12	86	117
13	79	108
14	74	100
15	69	93
17	61	82
19	54	74
21	49	67
23	45	61
25	41	56

LeMond Reno T *3423000*14.083*

FRAMESET

Main tubes	6066 T6 aluminum, fully butted	
Stays	6066 T6 aluminum, fully butted	
Color	Metallic Black/Red • White/Black decal • Black fade to carbon fork	
Fork	Bontrager Race	371 mm axle-crown length
Headset	Slimstack	25.4/34.0/30.0, 36.3 mm stack height

CONTROLS

Handlebar	Alloy Ergo	26.0 mm clamp diameter
Stem	Alloy quick change, direct connect	40.0 mm steerer clamp height
Shift levers	Shimano Tiagra STI Dual Control	
Brake levers	Integrated brake/shift	
Tape	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano Tiagra T	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur	Shimano 105 GS	
Crankset	Shimano Tiagra 52/42/30	74/130 mm bolt hole circle
Bottom bracket	Shimano BB-UN40	68 x 113 (shell x axle, mm), Square axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	Shimano HG50 12-25, 9spd	

WHEELSET

Front wheel	Alloy, QR hub, 32°, Matrix Aurora rim 299 mm 3x spokes, Velox 16mm rim strip	610mm E.R.D.
Rear wheel	Alloy, QR hub, 32°, Matrix Aurora RDR rim 293/294 mm 3x rear spokes, Velox 16mm rim strip	603 mm E.R.D.
Spokes	14G stainless	
Front tire	Bontrager Race Lite	700 x 25c
Rear tire	Bontrager Race Lite	700 x 25c
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	LeMond, alloy micro-adjust	27.2 mm outer diameter
Saddle	CRZ+ Road	
Seatpost binder	Alloy w/integral bolt	31.9 mm inner diameter
Brakes	Alloy dual pivot	
Pedals	Alloy road, sealed, w/clips and straps	9/16" axle
Additionals	2 water bottle mounts (1 bottle on 49), pump peg (not on 49, 51)	
Bike weight	21.5 lb/9.76 kg	

FIT *dimensions in MM, unless specified*

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		66.9	68.5	70.5	72.3	74.0	75.7	77.8
	cm	170	174	179	184	188	192	198
Handlebar	width	400	420	420	440	440	440	460
Stem	length	90	100	110	110	120	120	130
	angle	17	17	17	17	17	17	17
Headset spacers		20	20	20	20	20	20	20
Crank	length	170	170	170	175	175	175	175
Seatpost	length	330	330	330	330	330	330	330
Steerer	length	197.3	209.3	226.3	245.3	263.3	282.3	302.3

GEOMETRY *dimensions in MM, unless specified*

Head tube angle	72.0	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	63	60	57	59	59	56	56
Seat tube angle	74.0	73.8	73.3	73.0	72.5	72.5	72.0
Effective top tube	525	532	545	565	575	591	606
Seat tube	488	498	512	528	542	560	574
Standover	728	741	754	772	785	803	815
Wheelbase	972	974	980	989	993	1007	1015
Bottom bracket height	264	266	266	269	269	269	269
Chainstay	410	410	413	413	413	416	416
Head tube	105	117	134	153	171	190	210

GEARING

	30	42	52
12	66	93	115
13	61	85	106
14	57	79	98
15	53	74	92
17	47	65	81
19	42	58	72
21	38	53	66
23	35	48	60
25	32	44	55

LeMond Reno T women's *3423003*14.083*

FRAMESET

Main tubes	6066 T6 aluminum, fully butted	
Stays	6066 T6 aluminum	
Color	Silver/Pearl White • Blue/Silver decal • Black fade to carbon fork	
Fork	Bontrager Race	371 mm axle-crown length
Headset	Slimstack	25.4/34.0/30.0, 36.3 mm stack height

CONTROLS

Handlebar	Alloy Ergo	26.0 mm clamp diameter
Stem	Alloy quick change, direct connect	40.0 mm steerer clamp height
Shift levers	Shimano Tiagra STI Dual Control	
Brake levers	Integrated brake/shift	
Tape	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano Tiagra T	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur	Shimano 105 GS	
Crankset	Shimano Tiagra 52/42/30	74/130 mm bolt hole circle
Bottom bracket	Shimano BB-UN40	68 x 113 (shell x axle, mm), Square axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	Shimano HG50 12-25, 9spd	

WHEELSET

Front wheel	Alloy, QR hub, 32°, Matrix Aurora rim 299 mm 3x spokes, Velox 16mm rim strip	610mm E.R.D.
Rear wheel	Alloy, QR hub, 32°, Matrix Aurora RDR rim 293/294 mm 3x rear spokes, Velox 16mm rim strip	603 mm E.R.D.
Spokes	14G stainless	
Front tire	Bontrager Race Lite	700 x 25c
Rear tire	Bontrager Race Lite	700 x 25c
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	LeMond, alloy micro-adjust	27.2 mm outer diameter
Saddle	Oasis, women's	
Seatpost binder	Alloy w/integral bolt	31.9 mm inner diameter
Brakes	Alloy dual pivot	
Pedals	Alloy road, sealed, w/clips and straps	9/16" axle
Additionals	2 water bottle mounts (1 bottle on 49), pump peg (not on 49, 51)	
Bike weight	21.3 lb/9.67 kg	

FIT *dimensions in MM, unless specified*

Frame	Size	45	49	53
Rider height, in.		64.6	65.3	68.4
	cm	164	166	174
Handlebar	width	380	400	420
Stem	length	85	85	100
	angle	17	17	17
Headset spacers		20	20	20
Crank	length	165	165	170
Seatpost	length	330	330	330
Steerer	length	182.3	197.3	226.3

GEOMETRY *dimensions in MM, unless specified*

Head tube angle	71.0	71.3	72.0
Fork offset	45.0	45.0	45.0
Trail	69	68	63
Seat tube angle	75.0	74.0	73.3
Effective top tube	498	510	530
Seat tube	488	503	519
Standover	698	728	754
Wheelbase	963	964	975
Bottom bracket height	264	264	266
Chainstay	410	410	413
Head tube	90	105	134

GEARING

	30	42	52
12	66	93	115
13	61	85	106
14	57	79	98
15	53	74	92
17	47	65	81
19	42	58	72
21	38	53	66
23	35	48	60
25	32	44	55

LeMond Big Sky SLT *3456000*14.093*

FRAMESET

Main tubes	6066 T6 aluminum, fully butted	
Stays	6066 T6 aluminum, fully butted	
Color	Brushed Aluminum/Metallic Blue • White/Metallic Silver decal • Black fade-to-carbon fork	
Fork	Carbon fiber composite, alloy steerer	371.0 mm axle-crown length
Headset	Slimstack	25.4/34.0/30.0, 36.3 mm stack height

CONTROLS

Handlebar	Bontrager Flat Top	25.4 mm clamp diameter
Stem	Alloy quick change, adjustable rise, direct connect	40.0 mm steerer clamp height
Shift levers	Shimano Ultegra STI, adjustable reach	
Brake levers	Integrated brake/shift	
Tape	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano 105 T	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur	Shimano Ultegra GS	
Crankset	Shimano Ultegra 52/42/30	74/130 mm bolt hole circle
Bottom bracket	Shimano 105	68 x 118 (shell x axle, mm), Shimano splined axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	Shimano HG70 12-25, 9spd	

WHEELSET

Front wheel	Bontrager Select Road, 20°	593mm E.R.D.
	281 mm radial spokes, Velox 16mm rim strip	
Rear wheel	Bontrager Select Road, 24°	603 mm E.R.D.
	293/294 mm 2x rear spokes, Velox 16mm rim strip	
Spokes	DT 14g, ProLock brass nipples	
Front tire	Bontrager Race Lite HardCase	700 x 28c
Rear tire	Bontrager Race Lite HardCase	700 x 28c
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Suspension, alloy	27.2 mm outer diameter
Saddle	CRZ+ Road	
Seatpost binder	Alloy w/integral bolt	31.9 mm inner diameter
Brakes	Alloy dual pivot, cartridge pads	
Pedals	Shimano SPD M505, clipless	9/16" axle
Additionals	Tektro RX 2.0 Midline brake levers, 2 water bottle mounts	
Bike weight	21.8 lb/9.90 kg	

FIT *dimensions in MM, unless specified*

Frame	Size	47	52	55	57	61
Rider height, in.		68.3	69.0	69.6	71.9	73.4
	cm	174	175	177	183	186
Handlebar	width	400	420	440	440	460
Stem	length	105	105	105	105	105
	angle	30	30	30	30	30
Headset spacers		30	30	25	25	25
Crank	length	170	172.5	172.5	175	175
Seatpost	length	300	300	350	350	350
Steerer	length	212.3	237.3	257.3	277.3	297.3

GEOMETRY *dimensions in MM, unless specified*

Head tube angle	72.0	72.0	72.5	73.0	73.0
Fork offset	43.0	43.0	43.0	43.0	43.0
Trail	63	63	60	57	57
Seat tube angle	75.0	74.0	73.0	73.0	72.0
Effective top tube	515	530	545	565	590
Seat tube	331	398	434	469	510
Standover	654	704	732	762	792
Wheelbase	995	1000	1000	1015	1028
Bottom bracket height	267	267	267	267	267
Chainstay	430	430	430	430	430
Head tube	110	135	155	180	200

GEARING

	30	42	52
12	66	93	115
13	61	85	106
14	57	79	98
15	53	74	92
17	47	65	81
19	42	58	72
21	38	53	65
23	35	48	60
25	32	44	55

LeMond Big Sky SL *3457*

FRAMESET

Main tubes	6066 T6 aluminum, fully butted	
Stays	6066 T6 aluminum, fully butted	
Color	Brushed Al/Metallic Blue • White/Metallic Silver decal • Black-to-carbon fork	
Fork	Carbon fiber composite, alloy steerer	371.0 mm axle-crown length
Headset	Slimstack	25.4/34.0/30.0, 36.3 mm stack height

CONTROLS

Handlebar	Bontrager Flat Top	25.4 mm clamp diameter
Stem	Alloy quick change, adjustable rise, direct connect	40.0 mm steerer clamp height
Shift levers	Shimano 105 STI, Flite Deck compatible	
Brake levers	Integrated brake/shift	
Tape	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano 105 T	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur	Shimano 105 GS	
Crankset	Shimano 105 52/42/30	74/130 mm bolt hole circle
Bottom bracket	Shimano 105	68 x 118 (shell x axle, mm), Shimano splined axle
Chain	Shimano HG-73	9 speed, 108 links
Cassette	Shimano HG50 12-25, 9spd	

WHEELSET

Front wheel	Bontrager Select Road, 20°	593mm E.R.D.
	281 mm radial spokes, Velox 16mm rim strip	
Rear wheel	Bontrager Select Road, 24°	603 mm E.R.D.
	293/294 mm 2x rear spokes, Velox 16mm rim strip	
Spokes	DT 14g, ProLock brass nipples	
Front tire	Bontrager Race Lite HardCase	700 x 28c
Rear tire	Bontrager Race Lite HardCase	700 x 28c
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Suspension, alloy	27.2 mm outer diameter
Saddle	CRZ+ Road	
Seatpost binder	Alloy w/integral bolt	31.9 mm inner diameter
Brakes	Alloy dual pivot, cartridge pads	
Pedals	Shimano SPD M505, clipless	9/16" axle
Additionals	Tektro RX 2.0 Midline brake levers, 2 water bottle mounts	
Bike weight	21.8 lb/9.90 kg	

FIT *dimensions in MM, unless specified*

Frame	Size	47	52	55	57	61
Rider height, in.		68.3	69.0	69.6	71.9	73.4
	cm	174	175	177	183	186
Handlebar	width	400	420	440	440	460
Stem	length	105	105	105	105	105
	angle	30	30	30	30	30
Headset spacers		30	30	25	25	25
Crank	length	170	172.5	172.5	175	175
Seatpost	length	300	300	350	350	350
Steerer	length	212.3	237.3	257.3	277.3	297.3

GEOMETRY *dimensions in MM, unless specified*

Head tube angle	72.0	72.0	72.5	73.0	73.0
Fork offset	43.0	43.0	43.0	43.0	43.0
Trail	63	63	60	57	57
Seat tube angle	75.0	74.0	73.0	73.0	72.0
Effective top tube	515	530	545	565	590
Seat tube	331	398	434	469	510
Standover	654	704	732	762	792
Wheelbase	995	1000	1000	1015	1028
Bottom bracket height	267	267	267	267	267
Chainstay	430	430	430	430	430
Head tube	110	135	155	180	200

GEARING

	30	42	52
12	66	93	115
13	61	85	106
14	57	79	98
15	53	74	92
17	47	65	81
19	42	58	72
21	38	53	65
23	35	48	60
25	32	44	55

LeMond Big Sky S *3458*

FRAMESET

Main tubes	6066 T6 aluminum, fully butted	
Stays	6066 T6 aluminum, fully butted	
Color	Brushed Al/Metallic Blue • White/Metallic Silver decal • Black fade-to-carbon fork	
Fork	Carbon fiber composite, alloy steerer	371.0 mm axle-crown length
Headset	Slimstack	25.4/34.0/30.0, 36.3 mm stack height

CONTROLS

Handlebar	Bontrager Flat Top	25.4 mm clamp diameter
Stem	Alloy quick change, adjustable rise, direct connect	40.0 mm steerer clamp height
Shift levers	Shimano Sora STI Dual Control	
Brake levers	Integrated brake/shift	
Tape	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano Sora	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur	Shimano Tiagra GS	
Crankset	SR Superbe 52/42/30	74/130 mm bolt hole circle
Bottom bracket	Cartridge	68 x 118 (shell x axle, mm), Shimano splined axle
Chain	KMC Z-51	9 speed, 108 links
Cassette	SRAM PG850 12-26, 8spd	

WHEELSET

Front wheel	Alloy, QR hub, 32°, Alex AT450 rim 281 mm radial spokes, Velox 16mm rim strip	593mm E.R.D.
Rear wheel	Alloy, QR hub, 32°, Alex AT450 rim 293/294 mm 2x rear spokes, Velox 16mm rim strip	603 mm E.R.D.
Spokes	15G stainless	
Front tire	Bontrager Race Lite HardCase	700 x 28c
Rear tire	Bontrager Race Lite HardCase	700 x 28c
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Suspension, alloy	27.2 mm outer diameter
Saddle	CRZ+ Road	
Seatpost binder	Alloy w/integral bolt	31.9 mm inner diameter
Brakes	Alloy dual pivot, cartridge pads	
Pedals	Alloy road, sealed, w/clips and straps	9/16" axle
Additionals	Tektro RX 2.0 Midline brake levers, 2 water bottle mounts	
Bike weight	21.8 lb/9.90 kg	

FIT *dimensions in MM, unless specified*

Frame	Size	47	52	55	57	61
Rider height, in.		68.3	69.0	69.6	71.9	73.4
	cm	174	175	177	183	186
Handlebar	width	400	420	440	440	460
Stem	length	105	105	105	105	105
	angle	30	30	30	30	30
Headset spacers		30	30	25	25	25
Crank	length	170	172.5	172.5	175	175
Seatpost	length	300	300	350	350	350
Steerer	length	212.3	237.3	257.3	277.3	297.3

GEOMETRY *dimensions in MM, unless specified*

Head tube angle	72.0	72.0	72.5	73.0	73.0
Fork offset	43.0	43.0	43.0	43.0	43.0
Trail	63	63	60	57	57
Seat tube angle	75.0	74.0	73.0	73.0	72.0
Effective top tube	515	530	545	565	590
Seat tube	331	398	434	469	510
Standover	654	704	732	762	792
Wheelbase	995	1000	1000	1015	1028
Bottom bracket height	267	267	267	267	267
Chainstay	430	430	430	430	430
Head tube	110	135	155	180	200

GEARING

	30	42	52
12	66	93	115
13	61	85	106
14	57	79	98
15	53	74	92
17	47	65	81
19	42	58	72
21	38	53	65
23	35	48	60
25	32	44	55

LeMond Poprad *3460000*14.063*

FRAMESET

Main tubes	Reynolds 853 Select	
Stays	Reynolds 853 Select	
Color	Black Metallic • Blue decal	
Fork	X-Lite Cross, alloy	405 mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 26.5 mm stack height

CONTROLS

Handlebar	Bontrager Race CX	25.4 mm clamp diameter
Stem	Bontrager Select	41.0 mm steerer clamp height
Shift levers	Shimano 105 STI, Flite Deck compatible	
Brake levers	Integrated brake/shift	
Tape	Powercork	

DRIVETRAIN

Front derailleur	Shimano 105	Down pull, 31.8 mm/ 1 1/4" attachment
Rear derailleur	Shimano 105	
Crankset	Bontrager Select 53/39	130 mm bolt hole circle
Bottom bracket	TruVativ Isis	68 x 108 (shell x axle, mm), ISIS splined axle
Chain	Shimano HG-53	9 speed, 112 links
Cassette	Shimano HG50 12-25, 9spd	

WHEELSET

Front wheel	Bontrager Select Road, 20°	593mm E.R.D.
	281 mm radial spokes, Velox 16mm rim strip	
Rear wheel	Bontrager Select Road, 24°	603 mm E.R.D.
	293/294 mm 2x rear spokes, Velox 16mm rim strip	
Spokes	DT 14g, ProLock brass nipples	
Front tire	Bontrager Jones CX, 127tpi	700 x 32c
Rear tire	Bontrager Jones CX, 127tpi	700 x 32c
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Sport	27.2 mm outer diameter
Saddle	Titec Ithys Amore	
Seatpost binder	Alloy w/integral bolt, cable hanger	31.9 mm inner diameter
Brakes	Avid Shorty 4, cantilever	
Pedals	-not supplied-	9/16" axle
Additionals	2 water bottle mounts, Front cable hanger (10mm), Tektro RX 2.0 Mid-line brake levers	
Bike weight	21.8 lb/9.90 kg	

FIT *dimensions in MM, unless specified*

Frame	Size	49	52	55	57	59
Rider height, in.		67.7	70.5	72.0	74.5	75.8
	cm	172	179	183	189	192
Handlebar	width	420	440	460	460	460
Stem	length	90	105	105	120	120
	angle	5	10	10	10	10
Headset spacers		50	50	50	50	40
Crank	length	170	170	175	175	175
Seatpost	length	300	300	300	300	300
Steerer	length	198.5	213.5	22.5	246.0	254.5

GEOMETRY *dimensions in MM, unless specified*

Head tube angle	72.0	72.0	72.5	72.5	73.0
Fork offset	45.0	45.0	45.0	45.0	45.0
Trail	65	65	62	62	59
Seat tube angle	74.0	73.5	73.0	72.5	72.5
Effective top tube	525	542	562	578	590
Seat tube	519	549	578	598	618
Standover	776	795	817	833	852
Wheelbase	992	1004	1015	1025	1033
Bottom bracket height	269	269	269	269	269
Chainstay	430	430	430	430	430
Head tube	85	100	116	133	151

GEARING

	39	**53**
12	88	119
13	81	110
14	75	102
15	70	95
17	62	84
19	55	75
21	50	68
23	46	62
25	42	57

LeMond Wayzata *3466000*14.063*

FRAMESET

Main tubes	Reynolds 853 Select	
Stays	Reynolds 853 Select	
Color	Silver Metallic • Blue decal	
Fork	X-Lite Cross, alloy	405 mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 26.5 mm stack height

CONTROLS

Handlebar	Bontrager Select	25.4 mm clamp diameter
Stem	Bontrager Sport	41.0 mm steerer clamp height
Shift levers	Shimano R440 RapidFire	
Brake levers	Avid FR-1	
Grips	Serfas dual density	

DRIVETRAIN

Front derailleur	Shimano Tiagra T	Down pull, 31.8 mm/ 1 1/4" attachment
Rear derailleur	Shimano Tiagra GS	
Crankset	Bontrager Sport 52/42/30	74/130 mm bolt hole circle
Bottom bracket	Shimano BB-UN40	68 x 118 (shell x axle, mm), Square axle
Chain	Shimano HG-53	9 speed, 112 links
Cassette	Shimano HG50 12-25, 9spd	

WHEELSET

Front wheel	Bontrager Select Road, 20°	593mm E.R.D.
	281 mm radial spokes, Velox 16mm rim strip	
Rear wheel	Bontrager Select Road, 24°	603 mm E.R.D.
	293/294 mm 2x rear spokes, Velox 16mm rim strip	
Spokes	DT 14g, ProLock brass nipples	
Front tire	Bontrager Race Lite HardCase	700 x 25c
Rear tire	Bontrager Race Lite HardCase	700 x 25c
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Sport	27.2 mm outer diameter
Saddle	Bontrager	
Seatpost binder	Alloy w/integral bolt	31.9 mm inner diameter
Brakes	Avid Single Digit 3, linear pull	
Pedals	Shimano SPD M505, clipless	9/16" axle
Additionals	2 water bottle mounts, Tektro RX 2.0 Mid-line brake levers	
Bike weight	24.5 lb/11.12 kg	

FIT *dimensions in MM, unless specified*

Frame	Size	49	52	55	57	59
Rider height, in.		67.4	70.0	71.6	74.1	75.6
	cm	171	178	182	188	192
Handlebar	width	600	600	600	600	600
Stem	length	90	105	105	120	120
	angle	15	15	15	15	15
Headset spacers		30	30	30	30	30
Crank	length	170	170	175	175	175
Seatpost	length	300	300	300	300	300
Steerer	length	178.5	193.5	209.5	226	244.5

GEOMETRY *dimensions in MM, unless specified*

Head tube angle	72.0	72.0	72.5	72.5	73.0
Fork offset	45.0	45.0	45.0	45.0	45.0
Trail	65	65	62	62	59
Seat tube angle	74.0	73.5	73.0	72.5	72.5
Effective top tube	525	542	562	578	590
Seat tube	519	549	578	598	618
Standover	776	795	817	833	852
Wheelbase	992	1004	1015	1025	1033
Bottom bracket height	269	269	269	269	269
Chainstay	430	430	430	430	430
Head tube	85	100	116	133	151

GEARING

	30	42	52
12	68	95	117
13	62	87	108
14	58	81	100
15	54	76	94
17	48	67	83
19	43	60	74
21	39	54	67
23	35	49	61
25	32	45	56