



AERO ROAD IN-ROUTE STEM

AERO ROAD STEM – IN-ROUTE

SPEC TABLE	AERO ROAD STEM			
Material	Carbon Fiber			
Length, Reach, Stack, Weight	Length	Reach	Stack	Weight
	80mm	79.8	12.5	170g
	90mm	89.7	10.4	176g
	100mm	99.5	8.2	177g
	110mm	109.3	5.8	179g
	120mm	119.1	3.4	190g
	130mm	128.9	0.8	194g
Rise	-7			
Clamp Diameter	31.8mm			
Steer Tube Clamp Diameter	1 1/8"			
Face Plate Material	Aluminum			
Hardware Material	Titanium			
Torque Spec: Face Plate	6Nm			
Torque Spec: Steer Tube	6Nm			
Cable Routing	IN-Route System			
Computer Mount	ENVE K Edge Aero Road Computer Mount			
Spacers	Round Spacer			
Max Spacer Height	40mm			
PART NUMBER				
300-1029-018	80mm Stem Aero IN-Route, -7 deg			
300-1029-019	90mm Stem Aero IN-Route, -7 deg			
300-1029-020	100mm Stem Aero IN-Route, -7 deg			
300-1029-021	110mm Stem Aero IN-Route, -7 deg			
300-1029-022	120mm Stem Aero IN-Route, -7 deg			
300-1029-023	130mm Stem Aero IN-Route, -7 deg			

The SES Aero Road Riser Stem was designed to achieve a rider's ideal position without the need of excessive spacers. This stem can provide 43.5 – 49mm of stack and does so by increasing the stack height of the stem's steerer clamp and a positive stem angle.