

2017 Front Suspension Specifications

Oil Volume, Air Pressure, Coil Spring Rates, and Configurations

GEN.00000000005176 Rev E
© 2022 SRAM, LLC

TABLE OF CONTENTS

Oil Volume and Lubricant **3**

Air Spring Pressure **6**

Coil Spring Rates **10**

Configurations **11**

Use ONLY RockShox, SRAM, and Maxima suspension oils/fluids and grease, unless otherwise specified. Use of any other lubricants can damage seals and decrease performance.

Refer to the appropriate RockShox suspension fork service manual, available at www.sram.com/service, for service specifications and procedures.

Oil Volume and Lubricant

		DAMPER						SPRING							
		Damper	Upper Tube			Lower Leg		Spring	Upper Tube				Lower Leg		
FORK	MODEL		Oil	Oil Height‡ (mm)	Volume (mL)	Oil**	Volume (mL)		Oil**	Volume (mL)	Grease	Grease Application	Oil**	Volume (mL)
30 Gold	RL 26	Motion Control	RockShox 5wt	80-85	85	RockShox 15wt	5	Solo Air	RockShox 5wt	3-6 (positive)	PM600 or SRAM Butter	Air Piston	RockShox 15wt	10
	RL 27.5				102									
	RL 29													
30 Silver	TK 26	TurnKey	RockShox 5wt	80-85	100	RockShox 15wt	5	Solo Air	RockShox 5wt	3-6 (positive)	PM600 or SRAM Butter	Air Piston	RockShox 15wt	10
	TK 27.5				123			Solo Air						
	TK 29				122			Coil	-	-		Coil Spring		
Argyle	RC	Motion Control	RockShox 5wt	-	130	RockShox 15wt	10	Coil	-	-	PM600 or SRAM Butter	Coil Spring	RockShox 15wt	30
Bluto	RCT3	Motion Control	RockShox 5wt	71-77	106	RockShox 15wt	5	Solo Air	-	-	SRAM Butter	Air Piston	RockShox 15wt	5
	RL													
BoXXer	World Cup	Charger Damper	Maxima PLUSH 3wt	-	Bleed	Maxima PLUSH Dynamic Suspension Lube Light	10	Solo Air	-	-	SRAM Butter	Air Piston	Maxima PLUSH Dynamic Suspension Lube Light	10
	Team							Coil	-	-		Coil Spring		20
	RC	Motion Control IS	RockShox 5wt	95-104	290									
Domain	RC	Motion Control IS	RockShox 5wt	-	200	RockShox 15wt	10	Coil	-	-	SRAM Butter	Coil Spring	RockShox 15wt	30
Domain Dual Crown				103-109	325									40

*Boost
**Suspension oil/fluid - Maxima PLUSH Dynamic Suspension Lube and RockShox 0w-30 suspension oils are forward and backward compatible with RockShox Dynamic Seal Grease and SRAM Butter.
‡Oil Height - Measure from the top of the crown (above the upper tube) down to the oil.

Oil Volume and Lubricant

		DAMPER						SPRING							
			Upper Tube			Lower Leg			Upper Tube				Lower Leg		
FORK	MODEL	Damper	Oil	Oil Height‡ (mm)	Volume (mL)	Oil**	Volume (mL)	Spring	Oil**	Volume (mL)	Grease	Grease Application	Oil**	Volume (mL)
Lyrik	RC2 DH	Mission Control DH	RockShox 5wt	-	184	RockShox 15wt	10	Solo Air	-	-	SRAM Butter	Air Piston	RockShox 15wt	10
	RCT3	Charger Damper	Maxima PLUSH 3wt	-	Bleed	Maxima PLUSH Dynamic Suspension Lube Light		Solo Air Dual Position Air					Maxima PLUSH Dynamic Suspension Lube Light	
	RC													
Paragon Gold	RL	Motion Control	RockShox 5wt	80-85	87	RockShox 15wt	12	Solo Air	RockShox 5wt	3-6 (positive)	PM600 or SRAM Butter	Air Piston	RockShox 15wt	12
Paragon Silver	TK	Turnkey	RockShox 5wt	80-85	100	RockShox 15wt	12	Coil	-	-	PM600 or SRAM Butter	Coil Spring	RockShox 15wt	12
Pike	RCT3	Charger Damper	Maxima PLUSH 3wt	-	Bleed	Maxima PLUSH Dynamic Suspension Lube Light	10	Solo Air Dual Position Air	-	-	SRAM Butter	Air Piston	Maxima PLUSH Dynamic Suspension Lube Light	10
	RC													
	DJ							Solo Air						
Reba	RL	Motion Contol	RockShox 5wt	71-77	106	RockShox 15wt	5	Solo Air	-	-	SRAM Butter	Air Piston	RockShox 15wt	5
Recon Gold	RL	Motion Contol	RockShox 5wt	80-85	133	RockShox 15wt	6	Solo Air	RockShox 5wt	3-6 (positive)	PM600 or SRAM Butter	Air Piston	RockShox 15wt	6
	TK	TurnKey												
Recon Silver	RL	Motion Control	RockShox 5wt	80-85	118	RockShox 15wt	6	Solo Air	RockShox 5wt	3-6 (positive)	PM600 or SRAM Butter	Air Piston	RockShox 15wt	6
	RL B*				140									
	TK 26"	Turnkey			150									
	TK 27.5", 29"				118			Coil	-	-		Coil Spring		12

*Boost
**Suspension oil/fluid - Maxima PLUSH Dynamic Suspension Lube and RockShox 0w-30 suspension oils are forward and backward compatible with RockShox Dynamic Seal Grease and SRAM Butter.
‡Oil Height - Measure from the top of the crown (above the upper tube) down to the oil.

Oil Volume and Lubricant

		DAMPER						SPRING						
			Upper Tube			Lower Leg			Upper Tube				Lower Leg	
FORK	MODEL	Damper	Oil	Oil Height‡ (mm)	Volume (mL)	Oil**	Volume (mL)	Spring	Oil**	Volume (mL)	Grease	Grease Application	Oil**	Volume (mL)
Revelation	RCT3	Motion Control	RockShox 5wt	82-88	134	RockShox 15wt	5	Solo Air	-	-	SRAM Butter	Air Piston	RockShox 15wt	5
	RL													
RS-1	-	Accelerator Damper	RockShox 5wt	-	Bleed	RockShox 15wt	5-10	Solo Air	-	-	SRAM Butter	Air Piston	RockShox 15wt	5-10
Sektor Gold	RL	Motion Control	RockShox 5wt	80-85	130	RockShox 15wt	5-8	Solo Air	RockShox 5wt	3-6 (positive)	PM600 or SRAM Butter	Air Piston	RockShox 15wt	3-8
					125			Dual Position Coil	-	-		Coil Spring		10-16
Sektor Silver	RL	Motion Control	RockShox 5wt	80-85	150	RockShox 15wt	6	Solo Air	RockShox 5wt	3-6 (positive)	PM600 or SRAM Butter	Air Piston	RockShox 15wt	6
	RL Boost				140									
SID	RLC	Charger Damper	Maxima PLUSH 3wt	-	Bleed	RockShox 15wt	5	Solo Air	-	-	SRAM Butter	Air Piston	RockShox 15wt	5
	World Cup													
	RL	Motion Control	RockShox 5wt	71-77	100									
	XX													
XC 30	TK	TurnKey	RockShox 5wt	80-85	143	-	-	Coil	-	-	PM600 or SRAM Butter	Coil Spring	-	-
Yari	RC	Motion Control	RockShox 5wt	100-106	180	Maxima PLUSH Dynamic Suspension Lube Light	10	Solo Air	-	-	SRAM Butter	Air Piston	Maxima PLUSH Dynamic Suspension Lube Light	10
								Dual Position Air						

*Boost
**Suspension oil/fluid - Maxima PLUSH Dynamic Suspension Lube and RockShox 0w-30 suspension oils are forward and backward compatible with RockShox Dynamic Seal Grease and SRAM Butter.
‡Oil Height - Measure from the top of the crown (above the upper tube) down to the oil.

Air Spring Pressure

FORK	AIR SPRING	WHEEL (in)	TRAVEL (mm)	<140 lbs (<63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)	>220 lbs (>99 kg)	MAX PSI
				E-Bikes Add 10 psi						
30 Gold	Solo Air	26 27.5 29	80	90-110 psi	110-125 psi	125-140 psi	140-160 psi	160+ psi	-	265 psi
			100	50-70 psi	70-85 psi	85-100 psi	100-120 psi	120+ psi	-	205 psi
		27.5 29	120							
30 Silver	Solo Air	26 27.5 29	80	90-110 psi	110-125 psi	125-140 psi	140-160 psi	160+ psi	-	265 psi
			100	50-70 psi	70-85 psi	85-100 psi	100-120 psi	120+ psi	-	205 psi
		27.5	120							
Bluto	Solo Air	26	80 100 120	70-90 psi	90-105 psi	105-120 psi	120-135 psi	135+ psi	-	200 psi
BoXXer World Cup	Solo Air	26 27.5	200	50-65 psi	65-80 psi	80-95 psi	95-110 psi	110-125 psi	125+ psi	165 psi
Lyrik	Solo Air	27.5 27.5B*	160	45-55 psi	55-65 psi	65-75 psi	75-85 psi	85-95 psi	95+ psi	148 psi
		29 29B*/27.5+	150 160							
		26	170							
		27.5 27.5B* 29 29B*/27.5+	170 180	35-45 psi	45-55 psi	55-65 psi	65-75 psi	75-85 psi	85+ psi	148 psi
	Dual Position Air	27.5 27.5B*	160	55-65 psi	65-75 psi	75-85 psi	85-95 psi	95-105 psi	105+ psi	163 psi
		29 29B*/27.5+	150 160							
		27.5 27.5B*	170 180	45-55 psi	55-65 psi	65-75 psi	75-85 psi	85-95 psi	95+ psi	148 psi

*Boost

Air Spring Pressure

FORK	AIR SPRING	WHEEL (in)	TRAVEL (mm)	<140 lbs (<63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)	>220 lbs (>99 kg)	MAX PSI
				E-Bikes Add 10 psi						
Pike	Solo Air	27.5 27.5B* 29 29B*/27.5+	120	65-75 psi	75-85 psi	85-95 psi	95-105 psi	105-115 psi	115+ psi	163 psi
		29+								178 psi
		27.5 27.5B* 29 29B*/27.5+ 29+	130 140	55-65 psi	65-75 psi	75-85 psi	85-95 psi	95-105 psi	105+ psi	163 psi
		26 27.5 27.5B* 29 29B*/27.5+ 29+	150 160	45-55 psi	55-65 psi	65-75 psi	75-85 psi	85-95 psi	95+ psi	148 psi
	Dual Position Air	26 27.5 27.5B* 29 29B*/27.5+	150 160	45-65 psi	65-85 psi	85-105 psi	105-125 psi	125-145 psi	145+ psi	248 psi
		29+	150 160	55-65 psi	65-75 psi	75-85 psi	85-95 psi	95-105 psi	105+ psi	163 psi
Pike DJ	Solo Air	26	100	100-115 psi	115-130 psi	130-145 psi	145-160 psi	160-175 psi	175+ psi	250 psi
			140	65-75 psi	75-85 psi	85-95 psi	95-105 psi	105-115 psi	115+ psi	163 psi
Reba	Solo Air	29 29B*/27.5+	80	70-90 psi	90-105 psi	105-120 psi	120-135 psi	135+ psi	-	200 psi
		27.5 27.5B* 29 29B*/27.5+	100 120							

*Boost

Air Spring Pressure

FORK	AIR SPRING	WHEEL (in)	TRAVEL (mm)	<140 lbs (<63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)	>220 lbs (>99 kg)	MAX PSI
				E-Bikes Add 10 psi						
Recon Gold	Solo Air	27.5 29	80	90-110 psi	110-125 psi	125-140 psi	140-160 psi	160+ psi	-	265 psi
			100 120	50-70 psi	70-85 psi	85-100 psi	100-120 psi	120+ psi	-	205 psi
Recon Silver	Solo Air	27.5 29	80	90-110 psi	110-125 psi	125-140 psi	140-160 psi	160+ psi	-	265 psi
		26	100	50-70 psi	70-85 psi	85-100 psi	100-120 psi	120+ psi	-	205 psi
		27.5 27.5 B* 29 29 B*/27.5+	100 120							
Revelation	Solo Air	29 29B*/27.5+	120	65-85 psi	75-100 psi	85-115 psi	95-125 psi	125+ psi	-	190 psi
		27.5 27.5B* 29 29B*/27.5+	130 140							
		27.5 27.5B*	150							
RS-1	Solo Air	27.5 29 29+	100 120	70-90 psi	90-105 psi	105-120 psi	120-135 psi	135+ psi	-	200 psi
Sektor Gold	Solo Air	27.5 29	130 140 150	40-60 psi	60-75 psi	75-90 psi	90-105 psi	105+ psi	-	225 psi
Sektor Silver	Solo Air	27.5 27.5B* 29 29B*/27.5+	130 140	50-70 psi	70-85 psi	85-100 psi	100-120 psi	120+ psi	-	200 psi
		27.5B*	150							

*Boost

Air Spring Pressure

FORK	AIR SPRING	WHEEL (in)	TRAVEL (mm)	<140 lbs (<63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)	>220 lbs (>99 kg)	MAX PSI
				E-Bikes Add 10 psi						
Yari	Solo Air	27.5 27.5B* 29 29B*/27.5+	120 130 140	55-65 psi	65-75 psi	75-85 psi	85-95 psi	95-105 psi	105+ psi	163 psi
		29+	120	65-75 psi	75-85 psi	85-95 psi	95-105 psi	105-115 psi	115+ psi	178 psi
			130 140	55-65 psi	65-75 psi	75-85 psi	85-95 psi	95-105 psi	105+ psi	163 psi
		27.5 27.5B* 29 29B*/27.5+ 29+	150 160	45-55 psi	55-65 psi	65-75 psi	75-85 psi	85-95 psi	95+ psi	148 psi
		27.5 27.5B* 29 29B*/27.5+	170 180	35-45 psi	45-55 psi	55-65 psi	65-75 psi	75-85 psi	85+ psi	148 psi
	Dual Position Air	27.5 27.5B* 29 29B*/27.5+ 29+	150 160	55-65 psi	65-75 psi	75-85 psi	85-95 psi	95-105 psi	105+ psi	163 psi
		27.5 27.5B*	170 180	45-55 psi	55-65 psi	65-75 psi	75-85 psi	85-95 psi	95+ psi	148 psi

FORK	AIR SPRING	WHEEL (in)	TRAVEL (mm)	<120 lbs (<55 kg)	120-140 lbs (55-63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	>200 lbs (>90 kg)	MAX PSI
				E-Bikes Add 10 psi						
SID	Solo Air	29 29B*/27.5+	80 100	<70 psi	70-90 psi	90-105 psi	105-120 psi	120-135 psi	135+ psi	195 psi
		27.5 27.5B*	100							

FORK	AIR SPRING	WHEEL	TRAVEL (mm)	-	<132 lbs (<60 kg)	132-155 lbs (60-70 kg)	155-176 lbs (70-80 kg)	176-198 lbs (80-90 kg)	>198 lbs (>90 kg)	MAX PSI
				E-Bikes Add 10 psi						
Paragon Gold	Solo Air	700c	50 65	-	80-90 psi	90-100 psi	100-125 psi	125-135 psi	135+ psi	165 psi

*Boost

Coil Spring Rates

FORK	<140 lbs (<63 kg)		140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)
30 Silver	Not Available	Silver X-Soft	Yellow Soft	Red Medium	Blue Firm	Black X-Firm
Argyle	Yellow Soft	Red Medium	Blue Firm	Black X-Firm	Not Available	Pink XXX-Hart
BoXXer	Not Available	Silver X-Soft	Yellow Soft	Red Medium	Blue Firm	Black X-Firm
Domain						
Domain Dual Crown						
Recon Silver						
Sektor Gold						
XC 30						

Configurations

FORK	WHEEL (in)	TRAVEL (mm)	STEERER TUBE (in)		AXLE	OFFSET (mm)		AXLE to CROWN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)
30 Gold	26	80	1 1/8 Aluminum		9mm QR	39		453	185	680	58
		100						473			
	27.5	80	Tapered	1 1/8 Aluminum		42		468		710	62
		100						488			
		120						508			
	29	80				46	51	487		755	
		100						507			
		120	Tapered					527			
30 Silver	26	80	Tapered	1 1/8 Aluminum	9mm QR	39		455	185	680	58
		100						475			
	27.5	80				42		470		710	62
		100						490			
		120						510			
	29	80				46	51	489		755	
		100						509			
Argyle	26	100	1 1/8 Aluminum		20mm x 110mm	40		480	203	697	68
Bluto	26	80	Tapered		15mm x 150mm	51		491	215	760	116
		100						511			
		120						531			
BoXXer	26	200	1 1/8 Aluminum		20mm x 110mm	42		568	210	696	-
	27.5					48		581		720	
Domain	26	180	1 1/8 Steel		20mm x 110mm	40		565	203	698	70

*Boost

Configurations

FORK	WHEEL (in)	TRAVEL (mm)	STEERER TUBE (in)	AXLE	OFFSET (mm)	AXLE to CROWN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)
Domain Dual Crown	26	200	1 1/8 Aluminum	20mm x 110mm	42	568	210	696	-
	27.5				48	581		720	
Lyrik	26	170	Tapered	20mm x 110mm	40	545	215	698	70
	27.5	160		15mm x 100mm	42	552		714	66
		170				562			
		180				572			
	27.5B*	160		15mm x 110mm	42 / 46	552			81
		170				562			
		180				572			
	29	150		15mm x 100mm	51	561		752	66
		160				571			
		170				581			
		180				591			
	29B*/27.5+	150		15mm x 110mm		561			81
		160				571			
		170				581			
		180				591			
Paragon	700c	50	Tapered / 1 1/8 Aluminum / 1 1/8 Steel / 1 1/8 Steel XL	9mm QR	46	462	180	716	45
		65				477			
Pike DJ	26	100	Tapered	15mm x 100mm	40	482	215	694	66
		140				522			

*Boost

Configurations

FORK	WHEEL (in)	TRAVEL (mm)	STEERER TUBE (in)	AXLE	OFFSET (mm)		AXLE to CROWN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)
Pike	26	150	Tapered	15mm x 100mm	40		532	210	694	66
		160					542			
	27.5	120			42	46	512		714	
		130					522			
		140					532			
		150					542			
		160					552			
	27.5B*	120		15mm x 110mm			512	215		81
		130					522			
		140					532			
		150					542			
		160					552			
	29	120		15mm x 100mm	46	51	531	210	752	66
		130					541			
		140					551			
		150					561			
		160					571			

*Boost

Configurations

FORK	WHEEL (in)	TRAVEL (mm)	STEERER TUBE (in)		AXLE		OFFSET (mm)		AXLE to CROWN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)
Pike	29B*/27.5+	120	Tapered		15mm x 110mm		51		531	210	752	81
		130							541			
		140							551			
		150							561			
		160							571			
	29+	120							543	215	786	82
		130							553			
		140							563			
		150							573			
		160							583			
Reba	27.5	100	Tapered	1 1/8 Aluminum	9mm QR	15mm x 100mm	42		487	215	710	62
		120							507			
	27.5B*	100	Tapered		15mm x 110mm				487		712	81
		120							507			
	29	80	Tapered	1 1/8 Aluminum	9mm QR	15mm x 100mm	46	51	486		755	62
		100							506			
		120							526			
	29B*/27.5+	80	Tapered		15mm x 110mm		51		491		760	81
		100							511			
		120							531			

*Boost

Configurations

FORK	WHEEL (in)	TRAVEL (mm)	STEERER TUBE (in)	AXLE	OFFSET (mm)		AXLE to CROWN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)
Recon Gold	27.5	80	1 1/8 Aluminum	9mm QR	42		469	200	710	62
			Tapered	15mm x 100mm				215		
		100	1 1/8 Aluminum	9mm QR			489	200		
			Tapered	15mm x 100mm				215		
		120	1 1/8 Aluminum	9mm QR			509	200		
			Tapered	15mm x 100mm				215		
	29	80	1 1/8 Aluminum	9mm QR	46	51	486	215	753	
			Tapered	15mm x 100mm			488			
		100	1 1/8 Aluminum	9mm QR			506			
			Tapered	15mm x 100mm			508			
		120					528			

*Boost

Configurations

FORK	WHEEL (in)	TRAVEL (mm)	STEERER TUBE (in)			AXLE	OFFSET (mm)		AXLE to CROWN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)
Recon Silver	26	100	1 1/8 Aluminum			9mm QR	40		490	200	710	62
	27.5	80	1 1/8 Aluminum		1 1/8 Steel	9mm QR	42		466	203		
			Tapered			15mm x 100mm						
		100	1 1/8 Aluminum		1 1/8 Steel	9mm QR			486			
			Tapered			15mm x 100mm						
		120	1 1/8 Aluminum			9mm QR			506			
			Tapered			15mm x 100mm						
	27.5B*	80	Tapered			15mm x 110mm			469	215	712	81
		100							489			
		120							509			
	29	80	Tapered	1 1/8 Aluminum	1 1/8 Steel	9mm QR	51		485	203	755	62
						15mm x 100mm	46	51				
		100				9mm QR	51		505			
						15mm x 100mm	46	51				
		120	Tapered						525			
	29B*/27.5+	80	Tapered			15mm x 110mm	51		489	215	760	81
		100							509			
		120							529			

*Boost

Configurations

FORK	WHEEL (in)	TRAVEL (mm)	STEERER TUBE (in)	AXLE	OFFSET (mm)	AXLE to CROWN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)
Revelation	27.5	130	Tapered	15mm x 100mm	42	519	215	717	62
		140				529			
		150				539			
	27.5B*	130		15mm x 110mm		519		714	81
		140				529			
		150				539			
	29	120		15mm x 100mm	46 / 51	528		755	62
		130				538			
		140				548			
	29B*/27.5+	120		15mm x 110mm	51	530		760	81
		130				540			
		140				550			
RS-1	27.5	100	Tapered Carbon	Predictive Steering	42	487	215	710	62
		120				507			
	29	100			46 / 51	506		751	
		120				526			
	29+	100			51			780	82
SID	27.5	100	Tapered / Tapered Carbon	15mm x 100mm	42	487	215	714	62
	27.5B*		Tapered	15mm x 110mm					81
	29	80	Tapered / Tapered Carbon	15mm x 100mm	46 / 51	486		755	62
		100				506			
	29B*/27.5+	80	Tapered	15mm x 110mm	51	491			81
		100				511			

*Boost

Configurations

FORK	WHEEL (in)	TRAVEL (mm)	STEERER TUBE (in)			AXLE	OFFSET (mm)		AXLE to CROWN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)
Sektor Gold	27.5	130	Tapered			15mm x 100mm	42		519	215	717	62
		140							529			
		150							539			
	29	130					46	51	538		755	
		140							548			
Sektor Silver	27.5	130	Tapered			15mm x 100mm	42		520	215	717	62
		140							530			
	27.5B*	130				15mm x 110mm			520			81
		140							530			
		150							540			
	29	130				15mm x 100mm	46	51	539		752	62
		140							549			
	29B*/27.5+	130				15mm x 110mm	51		539		760	81
		140							549			
XC 30	27.5	80	Tapered	1 1/8 Aluminum	1 1/8 Steel	9mm QR	42		470	185	710	62
		100							490			
		120							510			
	29	80					46	51	489		755	
		100							509			

*Boost

Configurations

FORK	WHEEL (in)	TRAVEL (mm)	STEERER TUBE (in)	AXLE	OFFSET (mm)		AXLE to CROWN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)
Yari	27.5	120	Tapered	15mm x 100mm	42	46	512	215	714	66
		130					522			
		140					532			
		150					542			
		160					552			
		170					562			
		180					572			
	27.5B*	120		15mm x 110mm			512			81
		130					522			
		140					532			
		150					542			
		160					552			
		170					562			
		180					572			
	29	120		15mm x 100mm	51		531		752	66
		130					541			
		140					551			
		150					561			
		160					571			
		170					581			
		180					591			

*Boost

Configurations

FORK	WHEEL (in)	TRAVEL (mm)	STEERER TUBE (in)	AXLE	OFFSET (mm)	AXLE to CROWN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)
Yari	29B*/27.5+	120	Tapered	15mm x 110mm	51	531	215	786	81
		130				541			
		140				551			
		150				561			
		160				571			
		170				581			
		180				591			
	29+	120				543			82
		130				553			
		140				563			
		150				573			
		160				583			

*Boost

These are registered trademarks of SRAM, LLC:

1:1®, Accuwatt®, Avid®, ATAC®, AXS®, Bar®, Bioposition®, Blackbox®, BoXXer®, DoubleTap®, eTap®, Firecrest®, Firex®, Grip Shift®, GXP®, Holzfeller®, Hussefelt®, Iclic®, i-Motion®, Judy®, Know Your Powers®, NSW®, Omnium®, Osmos®, Pike®, PowerCal®, PowerLock®, PowerTap®, Qollector®, Quarq®, RacerMate®, Reba®, Rock Shox®, Ruktion®, Service Course®, ShockWiz®, SID®, Single Digit®, Speed Dial®, Speed Weaponry®, Spinscan®, SRAM®, SRAM APEX®, SRAM EAGLE®, SRAM FORCE®, SRAM RED®, SRAM RIVAL®, Stylo®, TIME®, Truvativ®, TyreWiz®, UDH®, Varicrank®, Velotron®, X0®, X01®, X-SYNC®, XX1®, Zipp®

These are registered logos of SRAM, LLC:

These are trademarks of SRAM:

10K™, 1X™, 202™, 30™, 30 Course™, 35™, 302™, 303™, 353™, 404™, 454™, 808™, 858™, 3ZERO MOTO™ , ABLC™, AeroGlide™, AeroBalance™, AeroLink™, Airea™, Air Guides™, AirWiz™, AKA™, AL-7050-TV™, Atmos™, Automatic Drive™, AxCad™, Axial Clutch™, Base™, BB5™, BB7™, BB30™, Bleeding Edge™, Blipbox™, BlipClamp™, BlipGrip™, Blips™, Bluto™, Bottomless Tokens™, ButterCup™, Cage Lock™, Carbon Bridge™, Centera™, Charger™, Charger 2™, Charger 3™, Charger Race Day™, Cleansweep™, Clickbox Technology™, Clics™, Code™, Cognition™, CoLab™, Connectamajig™, Counter Measure™, CYCLO™, DB8™, DD3™, DD3 Pulse™, DebonAir™, Deluxe™, Descendant™, DFour™, DFour91™, DH™, Dig Valve™, DirectLink™, Direct Route™, Domain™, DOT 5.1™, Double Decker™, Double Time™, Dual Flow Adjust™, Dual Position Air™, DUB™, DUB-PWR™, DZero™, E300™, E400™, Eagle™, E-Connect4™, ErgoBlade™, ErgoDynamics™, ESP™, EX1™, Exact Actuation™, Exogram™, Flight Attendant™, Flow Link™, FR-5™, Full Pin™, G2™, G40™, Giga Pipe™, Gnar Dog™, Guide™, GS™, GX™, Hammerhead™, Hard Chrome™, Hexfin™, HollowPin™, Howitzer™, HRD™, Hybrid Drive™, Hyperfoil™, i-3™, Impress™, Jaws™, Jet™, Kage™, Karoo™, Komfy™, LINK™, Lyrik™, MatchMaker™, Maxle™, Maxle 360™, Maxle DH™, Maxle Lite™, Maxle Lite DH™, Maxle Stealth™, Maxle Ultimate™, Micro Gear System™, Mini Block™, Mini Cluster™, Monarch™, Monarch Plus™, Motion Control™, Motion Control DNA™, MRX™, MX™, Noir™, NX™, OCT™, OmniCal™, OneLoc™, Paceline™, Paragon™, PC-1031™, PC-1110™, PC-1170™, PG-1130™, PG-1050™, PG-1170™, Piggyback™, Poploc™, Power Balance™, Power Bulge™, PowerChain™, PowerDomeX™, Powered by SRAM™, PowerGlide™, PowerLink™, Power Pack™, Power Spline™, Predictive Steering™, Pressfit™, Pressfit 30™, Prime™, Qalvin™, R2C™, Rapid Recovery™, Recon™, Reverb™, Revelation™, Riken™, Roller Bearing Clutch™, Rolling Thunder™, RS-1™, Rudy™, Rush™, RXS™, Sag Gradients™, Sawtooth™, SCT - Smart Coasterbrake Technology™, Seeker™, Sektor™, SHIFT™, ShiftGuide™, Shorty™, Showstopper™, SIDLuxe™, Side Swap™, Signal Gear Technology™, SL™, SL-70™, SL-70 Aero™, SL-70 Ergo™, SL-80™, Sl-88™, SLC2™, SL SPEED™, SL Sprint™, Smart Connect™, Solo Air™, Solo Spoke™, Speciale™, SpeedBall™, Speed Metal™, SRAM APEX 1™, SRAM Force 1™, SRAM RIVAL 1™, S-series™, Stealth-a-majig™, StealthRing™, Super-9™, Supercork™, Super Deluxe™, Super Deluxe Coil™, SwingLink™, SX™, Tangente™, TaperCore™, Timing Port Closure™, TSE Technology™, Tool-free Reach Adjust™, Top Loading Pads™, Torque Caps™, TRX™, Turnkey™, TwistLoc™, VCLC™, Vivid™, Vivid Air™, Vuka Aero™, Vuka Alumina™, Vuka Bull™, Vuka Clip™, Vuka Fit™, Wide Angle™, WiFLi™, X1™, X3™, X4™, X5™, X7™, X9™, X-Actuation™, XC™, X-Dome™, XD™, XDR™, XG-1150™, XG-1175™, XG-1180™, XG-1190™, X-Glide™, X-GlideR™, X-Horizon™, XLoc Sprint™, XPLR™, XPRESSO™, XPRO™, X-Range™, XX™, Yari™, ZEB™, Zero Loss™, ZM2™, ZR1™

Specifications and colors subject to change without prior notice.
© 2022 SRAM, LLC

This publication includes trademarks and registered trademarks of the following companies:

Boost™ is a trademark owned by Trek Bicycle Corporation.
PLUSH™ is a trademark owned by Maxima Racing Oils.

SRAM®

www.sram.com



ASIAN HEADQUARTERS
SRAM Taiwan
No. 1598-8 Chung Shan Road
Shen Kang Hsiang, Taichung City
Taiwan R.O.C.

WORLD HEADQUARTERS
SRAM LLC
1000 W. Fulton Market, 4th Floor
Chicago, Illinois 60607
U.S.A.

EUROPEAN HEADQUARTERS
SRAM Europe
Paasbosweg 14-16
3862ZS Nijkerk
The Netherlands