Puch continuously reviews its products for possible improvement, and reserves the right to change details and specifications without notice. 1986 Steyr-Daimler Puch, Inc. all rights reserved.

PUCH

Makers of World Class Wheels

Steyr-Daimler Puch, Inc., P.O. Box 108, Malone, NY 12953



RIDING SYSTEMS, FROM PUCH.

190	180	140	130/120	170	160	150
Chrome-moly double-butted, brazed-on cable guides, forged-type dropouts	Chrome-moly double-butted main tubes, brazed-on water bottle bosses	Triangle chrome-moly, brazed-on water bottle fittings and cable guides	High-tension steel, fully lugged with brazed-on fittings	Chrome-moly double-butted, forged dropouts, three set of brazed-on water bottle fittings and chain rest	Chrome-moly frame tubes, heliarc welded brazed-on cable guides and stops	High-tension steel frame, heliarc welded, brazed-on cable guides and two sets of water bottle fittings
Forged-type crown with retention device, forged-type dropouts	High-tension blades with box crown	High-tension steel with box crown	Box crown, high-tension blades	Forged crown and ends	High-tension unicrown	High-tension steel blades
Men's: 19", 21", 23", 25", 27" Ladies' Mixte: 19½"	Men's: 19", 21", 23", 25" Ladies' Mixte: 19½"	Men's: 19", 21", 23", 25" Ladies' Mixte: 19½"	130: Men's—19", 21", 23", 25" Ladies' Mixte or loop frame—19½" 120: Men's—18" Ladies' Mixte—18"	Men's: 19", 21", 23", 25"	Men's: 19½", 21½"	Men's: 19", 21", 23" Ladies' Mixte: 19"
Jet Black	Cherry Red	Blaze Red Electric Blue	130: Strobe Black, Blue Wave 120: (Men's) Blaze Red, (Ladies') Electric Blue	Cherry Red	Alpine Green, Fire	Royal Indigo
5MM foam cushion grips, black	5MM foam cushion grips, black	5MM foam cushion grips, black	5MM foam cushion grips, black	5MM foam cushion grips, black	5MM foam cushion grips, black	5MM foam cushion grips, black
27.1 lbs.	28 lbs.	29 lbs.	130: 30 lbs.	26.7 lbs.	31.5 lbs.	33 lbs.
Sealed headset, micro adjust	Tange sealed, micro adjust	Micro adjust	Micro adjust	Multi piece micro adjust	Micro adjust	MX-600MM micro adjust
Alloy ferrule, Puch engraved "Maes" pattern	Alloy ferrule, Puch engraved "Maes" pattern	Alloy ferrule, Puch engraved "Maes" pattern	Chrome plated, "Maes" pattern	SR CT-420 alloy with ferrule	Triangle cross braced chrome plated	Chrome plated steel, adjustable
Win alloy AH	Alloy aero style	SR 60/80/100 AH alloy	Chrome plated	SR CT-60/80/100MM aero style	Chrome-moly shaft incorporated	SR MTS-120 alloy double bolt clamp
Dia Compe side-pull alloy with extension levers quick release	Dia Compe, side-pull alloy with extension levers and quick release	Alloy aero side-pull, rubber lever hoods with extension levers	Alloy side-pull with extension levers	Dia Compe 960/155 with gum lever hoods	Alloy cantilever with motorcycle levers	Cantilever alloy with easy reach levers
Anatomic padded on nylon base	Anatomic padded on nylon base	Viscount vinyl on foam padded nylon base	Velo vinyl on foam padded nylon base	Anatomic touring	Viscount anatomic	VIC black anatomic padded
Alloy with allen key clamp	Alloy with allen bolt clamp	Steel, chrome plated with allen key clamp	Chrome plated with allen key clamp	SR CT-P5E alloy	Alloy fluted with quick release clamp	Chrome plated with allen key clamp
Sugino VP alloy cotterless forged, 40/52T satin finish chain rings	Sugino alloy cotterless, 42/52T satin finish chain rings	MIC alloy cotterless forged crank 42/52T steel chain rings	130: MIC cotterless forged alloy crank 120: Sugino No. 5 alloy crank	SR SAC-T310 30/45/50T alloy triple, forged	SR SAC-T310 alloy cotterless triple 48/38/28T chain rings	MIC alloy cotterless forged crank 42/52T steel chain rings
Alloy double-sided with reflectors	Alloy double-sided with reflectors	Alloy double-sided with reflectors	Chrome plated with reflectors	SR SP-153 single-sided alloy with toe clips and straps	A-2 chrome-moly shaft alloy double-sided with reflectors	Chrome plated with reflectors
Black	Black	Silver/black	Black	Silver/black	Gold/black	Chrome/black
6 Speed; 14/32 teeth	6 Speed; 14/32 teeth	14/28 teeth	Shimano 5 speed; 14/28 teeth	PS-6S; 13, 15, 18, 21, 25, 30 teeth	5 Speed, gold; 14/28 teeth	SunTour 6-speed; 13/30 teeth
7" Disc	7" Disc	7" Disc	7½" Chrome plated	7" Disc	7" Disc	7" Disc
SunTour SVX alloy with downtube shifters	SunTour AR-GT alloy with stem shifters	SunTour Seven with stem shifters	Shimano RS12 with stem shifters	SunTour Mount Tech II with downtube shifters	SunTour AG Tech alloy with handlebar controls	SunTour Seven with handlebar controls
12 Speed	12 Speed	10 Speed	10 Speed	18 Speed	15 Speed	12 Speed
Alloy quick release front with retention mechanism, bolt-on rear	Suzue light alloy, quick release front with chrome plated rear	Chrome plated quick release front, bolt-on rear	Chrome plated, semi-large flange	Alloy small flange quick release	Alloy bolt-on with sealed bearings	Chrome plated, semi-large flange
Araya SP-30, alloy 27" X 1¼"	Araya SP-30 alloy, 27" X 1¼"	Araya SP-30 silver alloy 27" X 1¼"	27" X 1¼" Chrome plated	Araya SP-30, 27" X 1¼" alloy	Sumo alloy 26" X 1.75"	Sumo 26" X 1.5" M-15 alloy
27" X 1¼" Gum wall 90 PSI high pressure	27" X 1¼" Gum wall with 90 PSI high pressure	27" X 1¼" Gum wall	27" X 1¼" Gum wall	27" X 1¼" Gum wall, 90 PSI	26" X 2.125" gum wall center rib, high traction	26" X 1.5" Gum wall black, semi-knobby
Stainless chain stay protector	Stainless chain stay protector	Downtube water bottle and cage, stainless chain stay protector	Stainless chain stay protector	Three water bottles and cages, alloy rear carrier	Brazed-on water bottle cage fittings	Downtube water bottle and cage

(NOTE)
For specifications on our Puch Austro-Daimler Mistral custom-built bicycles, see your dealer.

INTRODUCING WORLD CLASS

Take a close look at the new Puch bicycle specifications. The geometries are tight, the frames light, and matched components selected from all over the world.

But, whatever the mix, the result is a perfectly balanced riding system that's just about unbeatable in performance and value.

SPECIFICATIONS	A-D 360	A-D 300	A-D 280	A-D 260	A-D 230	A-D 210
FRAME:						
Frame:	Reynolds 531 throughout, complete braze-ons	Reynolds 501 combi frame, complete braze-ons	Reynolds 501 combi frame with braze-ons, including shift levers, pump peg	Reynolds 501 combi frame with braze-ons, downtube shift lever bosses, dropouts forged with adjuster	Reynolds 501 combi frame with braze-ons including lever bosses, dropouts forged with adjuster	Reynolds 500 combi frame, brazed-on brake cable guides, BB cable guides and stop on chain stay, dropout with hanger
Fork:	Forged sloping crown with forged dropouts	Forged sloping crown with forged dropouts	Forged sloping crown with forged dropouts	Forged semi-sloping crown with forged dropouts	Puch crown, dropouts with eye	Puch crown, dropouts with eye
Sizes:	Men's: 53, 55, 59, 63cm	Men's: 53, 55, 59, 63cm	Men's: 53, 55, 59, 63cm	Men's: 53, 55, 59, 63cm	Men's: 53, 55, 59, 63cm	Men's: 53, 55, 59, 63cm Ladies' Mixte: 53cm
Color:	Black Onyx. Over-lacquered, gold lining on head lube and fork crown, Puch script rear stay	Pearl Yellow. Over-lacquered, head lugs and fork crown with blue lining	Anthracite. Over-lacquered, head lugs and fork crown with gold lining	Cabernet. Over-lacquered, head lugs and fork crown with gold lining	Champagne Gold. Over-lacquered, head lugs and fork crown with brown lining	Sapphire or Carmine, head lugs and fork crown with gold lining
Tape:	Ambrosio White, Ergo tape	Ambrosio White, Ergo tape	Black cloth, heavy twill	Black cloth, heavy twill	Black cloth, heavy twill	Benotto Pearl Silver
Weight:	22.1 lbs.	22.5 lbs.	22.6 lbs.	23.9 lbs.	24 lbs.	26.5 lbs.
COMPONENTS:						
Headset:	Hatta micro adjust	Micro adjust	Micro adjust	Micro adjust	6 Piece micro adjust	6 Piece micro adjust
Handlebar:	SR CTD-420 L, engraved	SR CTD-420 L alloy with ferrule	SR CTD-420 L alloy with ferrule	Alloy engraved	Alloy engraved	Alloy engraved
Stem:	Win Medallion 55 and 59cm: 85MM, 63cm: 110MM	Win Medallion 55 and 59cm: 85MM, 63cm: 110MM	Win Sigma aero alloy 55cm: 80MM, 59 and 63cm: 100MM	Win Sigma aero alloy 55cm: 80MM, 59 and 63cm: 100MM	Win Sigma aero alloy 55cm: 80MM, 59 and 63cm: 100MM	Silver Win alloy 53cm and Mixte: 60MM, 55cm: 80MM, 59 and 63 cm: 100MM
Brakes:	Campagnolo Triumph, cables Campy grey	Weinmann 405 alloy with drilled levers, rubber hoods, wheel guides	Weinmann 405 alloy, short reach side-pull with drilled levers, rubber hoods	Weinmann alloy side-pull semi-automatic with drilled levers, rubber hoods	Weinmann 500 alloy short reach side-pull with drilled racing levers and rubber hoods	Weinmann 500 alloy, short reach side-pull, extension levers, with quick release, crystal cables
Saddle:	Concor red suede aero	Concor white leather aero	Anatomic suede	Dolphin anatomic, black	Anatomic black	Anatomic black
Seatpost:	Alloy micro adjust, fluted	Alloy micro adjust, fluted	Alloy micro adjust	Alloy micro adjust	SR-E105 alloy, fluted with allen key seat post clamp	SR-E105 alloy fluted, allen key seat post clamp
DRIVETRAIN:						
Crankset:	Campagnolo Triumph	Sugino DGS, all alloy forged, 42/52T chain rings	SR CRC-101 alloy forged	SR SAC-100 alloy forged, 42/52T alloy detachable chain rings	Shimano SAC 105, alloy forged, 42/52T alloy double detachable chain rings	SR SAC-310, one piece alloy cranks, 42/52T double detachable chain rings
Pedals:	Campagnolo Triumph	SR SP-153 alloy with toe clips and straps	SR SP-150 SE alloy with toe clips and straps	SR SP-154 alloy quill with reflectors	SR SP-467 alloy with double-sided reflectors	SR SP-467 alloy, double-sided with reflectors
Chain:	Gold	Gold	Gold	Gold	Gold	Black
Freewheel:	6 Speed gold; 14, 16, 18, 20, 22, 24 teeth	6 Speed gold; 14, 16, 18, 20, 23, 26 teeth	6 Speed gold; 14, 16, 20, 24, 26, 28 teeth	6 Speed; 14, 16, 20, 24, 26, 28 teeth	6 Speed; 14, 16, 18, 21, 24, 28 teeth	6 Speed; 14, 16, 18, 21, 24, 28 teeth
Spokeguard:	Alloy disc	Alloy disc	Alloy disc	Alloy disc	Alloy disc	Alloy disc
Derailleurs:	Campagnolo Triumph	Campagnolo Triumph	SunTour Le Pree (FD 3400, RD 6100, LD 4050), all alloy	SunTour ARX FD 2600, RD 4500, levers downtube top mount LD 2350	Shimano SAC 105 with brazed-on lever mounts on downtube	SunTour alloy SVX, FD 2500, RD 4200, with downtube shift levers
Speed:	12 Speed	12 Speed	12 Speed	12 Speed	12 Speed	12 Speed
WHEELS:						
Hubs:	Campagnolo Triumph	Alloy Lux Competition with sealed bearings, quick release front and rear	Alloy Lux Competition with sealed bearings, quick release front and rear	Atom alloy small flange, quick release front and rear	Atom alloy small flange, quick release front and rear	Atom alloy front and rear, with quick release front
Rims:	Weinmann 700C Super X concave, 514/124 with stainless steel spokes	Weinmann alloy 700C Super X concave, 514/124 with stainless steel spokes	Weinmann alloy 700C, Super X concave narrow section	Weinmann alloy 27" X 1⅛", narrow section	Weinmann alloy 416, 27" X 1¼"	Weinmann alloy 416, 27" X 1¼"
Tires:	Semperit 700 X 23C, high pressure gum wall	Semperit 700 X 23C, high pressure gum wall	Semperit 700 X 25C, high pressure gum wall	High pressure 27" X 1 1/16", 100 PSI gum wall	High pressure 27" X 1 1/16", 100 PSI gum wall	High pressure 27" X 1 1/16", 100 PSI gum wall
EXTRAS:						
	Water bottle and cage fittings on seat tube	Water bottle and cage fittings on seat tube	Bottle cage fittings on seat tube and downtube, stainless chain stay protector	Brazed-on downtube, bottle cage fittings and chain hanger	Brazed-on downtube, bottle cage fittings and chain hanger, stainless chain stay protector, brake mounted reflectors	Brazed-on bottle cage fittings, stainless chain stay protector, brake mounted reflectors

Puch continuously reviews its products for possible improvement, and reserves the right to change details and specifications without notice.

WORLD CLASS RIDING SYSTEMS

PUCH

SPECIFICATIONS

